CHARDER MOTECTION	
Some Martin	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) COMPLAINT/DISCOVERY (CI) RE-INSPECTION (FUI) ARMS COMPLAINT NO:								
AIRS ID#: 0251011 DATE: <u>4/2/2013</u> ARRIVE: <u>10:47 AM</u> DEPART: <u>1</u>	1:15 AM							
FACILITY NAME: ONE LOW PRICE CLEANERS								
FACILITY LOCATION: 8689 SW 24th Street								
MIAMI 33155-2337								
OWNER/AUTHORIZED REPRESENTATIVE: CARLOS MENDOZA PHONE: (305)265-0024 Email: Mobile: PHONE: Mobile: CONTACT NAME: PHONE: Mobile: Email: Mobile: PHONE: ENTITLEMENT PERIOD: 11/7/2010 / 11/7/2015 Mobile:								
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) ☑ IN COMPLIANCE								
PART II:FACILITY CLASSIFICATION (check \Box only one box in A)- Rule 62-213.300 FACA. 1.Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr 								

cleaning facility was 165.00 gallons.

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC					only o questio	
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A
2. Are all perc. containers leak free ?	\boxtimes	Yes		No		N/A
3. Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No		ľ
 Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal? 	\boxtimes	Yes		No		N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No	\boxtimes	N/A
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds		100		110	لالكا	11/12
b. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes		No	\boxtimes	N/A
	-					
PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)						
1. If the f acility classification is an existing small area source , no controls are required. Pr	rocee	ed to P	'art V	•		
2. If the facility classification is a new small area source , the machine should be equipped we condenser. Complete section A. below.	with a	a refrig	gerated	I		
3. If the fa cility classification is an existing large area source , the machine should be equip refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Camust have been installed prior to September 22, 1993</i>		with e n adsor		ł		
4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refrig	gerated	1		
A. Has the responsible official of all <u>existing large area & new sources</u> :			check ox for e		only o questio	
1. Equipped all machines with the appropriate vent controls?	\boxtimes	Yes		No		
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?	\boxtimes	Yes		No		N/A
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?		Yes		No		N/A
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?		Yes	\boxtimes	No		N/A
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?		Yes		No	\boxtimes	N/A
6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?		Yes	\boxtimes	No		

PA	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)				
B. 1.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes	🗌 No	
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly? a) Is the temperature differential equal to, or greater than 20° F?		Yes Yes	D No	□ N/A □ N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes	🗌 No	N/A
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes	🗌 No	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes	🗌 No	□ N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes	🗌 No	N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	🗌 No	N/A

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		(check 🗹 ox for each d	only one question)
1. Are receipts maintained for all perc purchased?	Yes	🗌 No	
2. Are rolling monthly total s of yearly perc consumption maintained ?	Yes	🗌 No	
3. Are leak detection inspection and repair reports maintained for the following:			
a) Of any leaks repaired w/in 24 hrs? or;	Yes	🗌 No	N/A
b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes	🗌 No	N/A
4. Is calibration data maintained for applicable direct reading instruments?	Yes	🗌 No	N/A
5. Is exhaust duct monitoring data on perc concentrations maintained?	Yes	🗌 No	N/A
6. Is a startup/shutdown/malfunction plan maintained for each machine?	Yes	🗌 No	
7. Are deviation reports maintained?	Yes	🗌 No	N/A
a) Problem corrected?	Yes	🗌 No	N/A
8. Is a compliance plan maintained , if applicable?	Yes	🗌 No	N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	(check	only one
1.	What type of leak detection equipment is used to detect leaks?	box for ea	ch question)
	Halogenated hydrocarbon detector PCE gas analyzer None used		
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to		
	the manufacturer's instructions (manual was available and RO could demonstrate		
	procedure) ? 🖂	Yes 🗌 N	0
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer		
	operated according to EPA Method 21 ?	Yes 🗌 N	o 🛛 N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of		
	each component interface where leakage could occur and moving it slowly along		
	the interface periphery?	Yes 🗌 N	0
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or		
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per		
	million by volume (based on documented specifications) ?	Yes 🗌 N	o N/A
6.	Is the halogenated hydrocarbon detector capable of detecting vapor concentrations		
	of PCE of 25 parts per million by volume (based on documented specifications) and		
	indicating a concentration of 25 parts per million by volume or greater by emitting		
	an audible or visual signal that varies as the concentration changes? $\hfill \hfill $	Yes 🗌 N	o N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn	mell or touch) v	while the
	system is in operation (§63.322(k))?		
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection of perce	otible leaks)
	b) Door gaskets and seating 🖾 Yes 🗌 No 🔲 N/A h) Stills 🖾 Yes		D D N/A D D N/A D D N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	genated hydroca	arbon detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parage	graph shall satisj	fy the
	requirements to conduct an inspection for perceptible leaks under $(3.322(k) \text{ or } (1))$		
	b) Door gaskets and seating Yes No N/A h) Stills C) c) Filter gaskets and seating Yes No N/A i) Exhaust dampers C) d) Pumps Yes No N/A j) Diverter valves Yes	Yes Down Yes No Yes No Yes No Yes No Yes No	D D N/A D D N/A D D N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)						
 9. What evidence suggests that leak checks are performed as required? 						
FRANK DELGADO	4/2/2013					
Inspector's Name (Please Print)	Date of Inspection					
	4/2014					
Inspector's Signature	Approximate Date of Next Inspection					
COMMENTS: NOV ISSUED FOR FAILURE TO PROVI THE DRY CLEANING MACHINE. THE NOV WAS MAILE THAT HE HAD THE RECORDS AT HOME. RECORDS WI CORRECTED.		DLD ME				

REVIEWED By Ray Gordon at 2:49 pm, Apr 22, 2013