

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2)	COMPLAINT/DISCOVERY (CI) ARMS COMPLAINT NO:
AIRS ID#: 0694830 DATE: <u>02/09/07</u>	ARRIVE: <u>9:30</u> DEPART: <u>10:05</u>
FACILITY NAME: QUALITY ONE PRICE CLEAN	ERS
FACILITY LOCATION: 620 W Highway 50	
CLERMONT 34711	
RESPONSIBLE OFFICIAL: BARBARA KING	PHONE: (352)394-3737
CONTACT NAME:	PHONE:
REMITTANCE YEAR: 2006 ENTIT	LEMENT PERIOD: 7/14/2005 / 7/14/2010 (effective date) (end date)
IN COMPLIANCE MINOR Non-COM	MPLIANCE SIGNIFICANT Non-COMPLIANCE
PART II: <u>FACILITY CLASSIFICATION</u> - Rule 62 (check 🗹 only one box in A)	-213.300 FAC
A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)	2. <u>New small area source</u> dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed on or after 12/9/91)
3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)	4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91)
5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits	
B. The total quantity of perchloroethylene (perc) p cleaning facility was 20 gallons.	purchased within the preceding 12 months by this dry

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box		
Does the responsible official of the dry cleaning facility:	for each question)		
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	□Yes □No ⊠N/A		
2. Examine the containers for leakage?	□Yes □ No □ N/A		
3. Close and secure machine doors except during loading/unloading?	🛛 Yes 🗌 No		
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A		
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	Yes No N/A		

PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)				
 If the facility classification is a <u>Existing small area source</u>, no controls are required. Proceed to Part V. 				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.			
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i>			
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped	with a ref	rigerated
А.	Has the responsible official of all <u>existing large area & new sources</u> :		a ☑ only each ques	one box for stion)
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes	No	⊠N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	□No	⊠N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes	□No	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- 🗌 Yes	□No	⊠N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	□No	

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)				
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)		
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No		
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	🗌 Yes 🗌 No 🛄 N/A		
	a) Is the temperature differential equal to, or greater than 20° F?	□Yes □ No □ N/A		
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A		
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A		
	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	- Yes No N/A		
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	🗌 Yes 🗌 No 🗌 N/A		
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A		
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC]		
	Does the responsible official: Call official: Call official: Call official:			
1.	Maintain receipts for perc purchased?	- 🛛 Yes 🗌 No		
2.	Maintain rolling monthly total of yearly perc consumption?	Yes No		
3.	Maintain leak detection inspection and repair reports for the following:			
	a) documentation of leaks repaired w/in 24 hrs? or;	- 🗌 Yes 🗌 No 🖾 N/A		
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A		

	6. Maintain a startup/shutdown/malfunction plan?	🛛 Yes 🗌 No	
	7. Maintain deviation reports?	🗌 Yes 🗌 No	N/A
	a) Problem corrected?	🗌 Yes 🗌 No	N/A
	8. Maintain a compliance plan, if applicable?	Yes No	N/A
-			

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

4. Maintain calibration data? (for applicable direct reading instruments) ------

5. Maintain exhaust duct monitoring data on perc concentrations? -----

(check \blacksquare only one box for each question)

Yes No N/A

 \Box Yes \Box No \boxtimes N/A

detection and repair inspection?	Xes No		
2. Does the facility maintain a leak log?	Xes No		
 3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves XYes No N/A g) Muck couplings, and valves Yes No N/A h) Stills b) Door gaskets and seating Yes No N/A h) Stills c) Filter gaskets and seating Yes No N/A i) Exhaust of Pumps Yes No N/A j) Diverter e) Solvent tanks and containers Yes No N/A k) Cartridg f) Water separators Yes No N/A 	Xes No N/A dampers Yes No N/A valves Yes No N/A		
4. Which method(s) of detection (is/are) used by the responsible official?			
 a) Visual examination (condensed solvent on exterior surfaces)			
Ferman Fletcher	02/09/07		
Inspector's Name (Please Print)	Date of Inspection		
02/0	08/08		
Inspector's Signature	Approximate Date of Next Inspection		
COMMENTS: Records not reviewed at the time of inspection must be sub	omitted		

Discharged vacuum water outside in the back of the facility Not all waste and perc product containers were kept in secondary containment