

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2 RE-INSPECTION (FU		· /
AIRS ID#: 0251033 DATE: <u>3/1/2012</u>	ARRIVE: <u>10:50 AM</u>	DEPART: <u>11:23 AM</u>
FACILITY NAME: REGENCY CLEANERS		
FACILITY LOCATION: 839 SW 132ND	AVE	
MIAMI 33184-	-1900	
OWNER/AUTHORIZED REPRESENTATIVE Email: GENCYRALPH@aol.com CONTACT NAME: RAFAEL AYALA Email: GENCYRALPH@aol.com ENTITLEMENT PERIOD: / (effective date) (en	Mobile:	E: (305)223-2342
PART I: INSPECTION COMPLIANCE STATE		NT Non-COMPLIANCE
PART II: FACILITY CLASSIFICATION (check ☑ only one box in A)	Rule 62-213.300 FAC	
 A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91) 3. Existing large area source dry-to-dry only, 140 ≤ x ≤ 2,100 g transfer only, 200 ≤ x ≤ 1,800 gal/yr (constructed before 12/9/91) 5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits 	fyr transfer only, $200 \le x$ both types, $140 \le x \le x$ (constructed on or after	40 gal/yr gal/yr l/yr r 12/9/91) e
B . The sum of the volume of all perchloroed cleaning facility was 45.00 gallons.	thylene (perc) purchases made in each of	of the previous 12 months by this dry

PA	ART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213,300 FAC		,	check x for o		only o	
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A
	Are all perc. containers leak free?	\boxtimes	Yes		No		N/A
	Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No		
	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?		Yes		No		N/A
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No	\boxtimes	N/A
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes		No		N/A
	ART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form) 1. If the f acility classification is an <u>existing small area source</u> , no controls are required. Proceedings of the procedure of the proce	rocee	ed to P	art V			
	2. If the facility classification is a new small area source , the machine should be equipped with a refrigerated condenser. Complete section A. below.						
	3. If the fa cility classification is an <u>existing large area source</u> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993						
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refriş	gerated	d 		
A.	Has the responsible official of all <u>existing large area & new sources</u> :					only o	
1.	Equipped all machines with the appropriate vent controls?	\boxtimes	Yes		No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?		Yes		No		N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	\boxtimes	Yes		No		N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	\boxtimes	Yes		No		N/A
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?		Yes		No	\boxtimes	N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	\boxtimes	Yes		No		

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes	□ N	Vo		
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?		Yes		No [_	N/A
	a) Is the temperature differential equal to, or greater than 20° F?	Ш	Yes	□ N	No [Ш	N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes	□ N	No [N/A
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes		lo [N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes	□ N	Vo [N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes		Jo [N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		lo [N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	□ N	No [N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	□ N	No [N/A
	Is airflow routed to the carbon adsorber (if used) at all times? ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC		(check vx for each	Z on	nly o	ne
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		(check vx for each	Z on	nly o	ne
P A			(bo	check vx for eac	on ch que	nly o	ne
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		(bo	check vx for eac	Zon ch que	nly o	ne
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————	\boxtimes	(bo	check vx for each	Zon ch que	nly or	ne
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————	\boxtimes	(bo Yes Yes	check vx for each	on on one of the original of t		ne n)
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————	\boxtimes	(bo Yes Yes	check 🔯 x for each	Z on ch que	hlly or	ne n) N/A
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes	check vx for each	Z on ch que	hlly or estion	ne n) N/A N/A
1. 2. 3. 4. 5.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes	check vx for each	Z on ch que	hlly or estion	ne n) N/A N/A
1. 2. 3. 4. 5. 6.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes	check x for each	Z on ch que lo	Inly or estion	ne n) N/A N/A
1. 2. 3. 4. 5. 6. 7.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes	check x for each	Z on ch que lo	Market State	ne n) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?	b	ox for each	question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	. Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ?	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery? $\ \ \ \ \ \ \ \ \ \ \ \ \ $	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes? \boxtimes	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sr	nell or	touch) whi	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection of the properties	pection	of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills		No No No No No No	 N/A N/A N/A N/A N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	enated	l hydrocarb	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	graph s	hall satisfy th	ne
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers	Yes Yes Yes Yes Yes	NoNoNoNoNoNoNo	 N/A N/A N/A N/A N/A

PART VI: LEAK DETECTION AND REPAIRS - Rule 6	62-213.300 FAC (continued)
9. What evidence suggests that leak checks are performed as ☐ Leak log documentation ☐ RO Assurances ☐ Explain other:	
FRANK DELGADO	3/1/2012
Inspector's Name (Please Print)	Date of Inspection
	3/2013
Inspector's Signature	Approximate Date of Next Inspection
COMMENTS: THE OWNER WAS ON SITE. I DID NOT FIND ANY LEAKS AROUND THE DRY CLEA ALL RECORDS WERE AVAILABLE AND FOUND LIP-TO	

REVIEWED

By Ray Gordon at 3:32 pm, Mar 26, 2012