

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

·	JAL (INS1, INS2)   SPECTION (FUI)	COMPLAINT/DISCOVE	· , , —		
AIRS ID#: 0251048 DATE: 4/	<u>5/2011</u>	ARRIVE: <u>12:25PM</u>	DEPART: <u>1:10PM</u>		
FACILITY NAME: ANN'S QU	JALITY CLEANERS				
FACILITY LOCATION:	2774 NW 46th Street				
	MIAMI 33142-3518				
		MCPHEE PHONE Mobile: PHONE Mobile: Mobile: Facility may be operating v	) <del>:</del>		
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box)  ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE					
PART II: FACILITY CLASSI  (check ☑ only one  A. 1. Existing small area of the small	source 140 gal/yr 2/9/91) source 5	<ul> <li>2. New small area source dry-to-dry only, x &lt; 14th transfer only, x &lt; 200 g both types, x &lt; 140 gala (constructed on or after</li> <li>4. New large area source</li> </ul>	0 gal/yr gal/yr /yr : 12/9/91)		
transfer only, 200 ≤ both types, 140 ≤ x (constructed before 1  5. Ineligible for Gene d rop store/out of bus facility exceeds above	a \( \le \) 1,800 gal/yr 2/9/91)  eral Permit	dry-to-dry only, $140 \le$ transfer only, $200 \le x$ both types, $140 \le x \le$ (constructed on or after	x ≤ 1,800 gal/yr 1,800 gal/yr		

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC			(check		only o	
		bo	ox for ea	ach q	uestic	on)
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	$\boxtimes$	Yes	_	No		N/A
2. Are all perc. containers leak free ?	$\boxtimes$	Yes		No		N/A
3. Are all machine doors kept closed and secured except during loading/unloading?	$\boxtimes$	Yes		No		
4. Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	. 🖂	Yes		No		N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.	- 🗆	Yes		No	$\boxtimes$	N/A
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?	- 🗆	Yes		No	$\boxtimes$	N/A
PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)						
1. If the f acility classification is an existing small area source, no controls are required.	Proces	ed to I	Part V			
1. If the Tacinty classification is an existing small area source, no controls are required.	TUCE	eu to 1	art v.			
2. If the facility classification is a <u>new small area source</u> , the machine should be equipped condenser. <b>Complete section A. below.</b>	l with	a refriș	gerated			
3. If the fa cility classification is an <b>existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> Carbon adsorber must have been installed prior to September 22, 1993						
4. If the facility classification is a <b>new large area source</b> , the machine should be equipped condenser. <b>Complete both sections A and B below.</b>	d with	a refri	gerated			
A. Has the responsible official of all existing large area & new sources:			(check l		only o	
1. Equipped all machines with the appropriate vent controls?	- 🖂	Yes		No		
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?		Yes		No		N/A
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	. 🖂	Yes		No		N/A
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?		Yes		No		N/A
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- 🗆	Yes		No	$\boxtimes$	N/A
6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	- 🖂	Yes		No		

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
B. For all existing large or new large area sources:							
	Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes	☐ No			
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?		Yes	□ No		N/A	
	a) Is the temperature differential equal to, or greater than $20^{\circ}$ F?		Yes	☐ No		N/A	
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes	☐ No		N/A	
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes	☐ No		N/A	
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes	☐ No		N/A	
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes	☐ No		N/A	
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	☐ No		N/A	
III							
	DT V. DECODDVEEDING DECUMENTED D. L. (2.212.200/2) EAG						
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		,	check 🗹 x for each	only o		
			,		•		
1.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Are receipts maintained for all perc purchased? ————————————————————————————————————	$\boxtimes$	bo	x for each	•		
1. 2.	Are receipts maintained for all perc purchased?	_	bo	x for each	•		
1. 2.	Are receipts maintained for all perc purchased?  Are rolling monthly total s of yearly perc consumption maintained?		bo	x for each	•		
1. 2.	Are receipts maintained for all perc purchased?  Are rolling monthly total s of yearly perc consumption maintained?  Are leak detection inspection and repair reports maintained for the following:		Yes Yes	x for each	•	on)	
1. 2. 3.	Are receipts maintained for all perc purchased?  Are rolling monthly total s of yearly perc consumption maintained?  Are leak detection inspection and repair reports maintained for the following:  a) Of any leaks repaired w/in 24 hrs? or;  b) Of any parts ordered to repair leak and leak repaired w/in 2 days		yes Yes Yes	x for each on the No No No	questic	on) N/A	
1. 2. 3.	Are receipts maintained for all perc purchased?		yes Yes Yes	x for each on the No No No No	questic	n) N/A N/A	
1. 2. 3. 4. 5.	Are receipts maintained for all perc purchased?		Yes Yes Yes Yes Yes	x for each on the No No No No No No	questic	N/A N/A N/A	
1. 2. 3. 4. 5. 6.	Are receipts maintained for all perc purchased?		Yes Yes Yes Yes Yes Yes	x for each of No No No No No No	questic	N/A N/A N/A	
1. 2. 3. 4. 5. 6.	Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes	x for each of No No No No No No	questic	N/A N/A N/A N/A	

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?	b	ox for each	question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ? 🖂	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery? $\boxtimes$	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes?	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn	nell or	touch) whil	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection	of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills S		<ul><li>□ No</li><li>□ No</li><li>□ No</li><li>□ No</li><li>□ No</li></ul>	<ul><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li></ul>
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	enated	l hydrocarbo	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	raph s	hall satisfy th	ie
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating  Yes  No N/A h) Stills Yes  No N/A i) Exhaust dampers	Yes Yes Yes Yes Yes	No   No   No   No   No   No   No	<ul><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li></ul>

PART VI: LEAK DETECTION AND REPAIRS – Rule 62	2-213.300 FAC (continued)	
9. What evidence suggests that leak checks are performed as ro  ☐ Leak log documentation ☐ RO Assurances ☐  Explain other:	equired?  On-site observation	
MARUFUL MALIK	4/5/2011	
Inspector's Name (Please Print)	Date of Inspection	
	4/5/2012	
Inspector's Signature	Approximate Date of Next Inspection	

**COMMENTS:** On April 5, 2011 I visited this facility to conduct the annual compliance inspection. On site I met Lionel Coney, the owner of the facility. No leaks were detected in the Dry Cleaning Machine. Perc purchase receipts and yearly perc consumption records were available. Halogen leak detector was available in working condition. Facility's Entitlement expired on August 18, 2010. Mr.Coney filled out AGP Notification Form in my presence.