

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

$\underline{\textbf{INSPECTION}}\ \underline{\textbf{TYPE}}\text{:} \text{ANNUAL (INS1, INS2)} \boxed{\boxtimes}$	COMPLAINT/DISCOVERY (CI)				
RE-INSPECTION (FUI)	ARMS COMPLAINT NO:				
AIRS ID#: 0251049 DATE: <u>01/21/2009</u>	ARRIVE: 1:25PM DEPART: 1:55PM				
FACILITY NAME: MIAMI DRY CLEANERS					
FACILITY LOCATION: 8410 W FLAGLER ST					
MIAMI 33144-2092					
OWNER/AUTHORIZED REPRESENTATIVE: MUI	HAMMAD QUADRI PHONE: (305)221-0585				
CONTACT NAME:	PHONE:				
ENTITLEMENT PERIOD: 4/14/2007 / 4/14/2012					
(effective date) (end date)					
PART I: INSPECTION COMPLIANCE STATUS (cf	neck 🗹 only one box)				
☐ IN COMPLIANCE ☐ MINOR Non-COMP	PLIANCE SIGNIFICANT Non-COMPLIANCE				
PART II: FACILITY CLASSIFICATION - Rule 62-2	13.300 FAC				
(check v only one box in A)	_				
A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr	2. New small area source dry-to-dry only, x < 140 gal/yr				
transfer only, $x < 200 \text{ gal/yr}$	transfer only, x < 200 gal/yr				
both types, $x < 140$ gal/yr (constructed before $12/9/91$)	both types, $x < 140 \text{ gal/yr}$ (constructed on or after 12/9/91)				
3. Existing large area source	4. New large area source				
dry-to-dry only, $140 \le x \le 2{,}100 \text{ gal/yr}$ transfer only, $200 \le x \le 1{,}800 \text{ gal/yr}$	dry-to-dry only, $140 \le x \le 2{,}100$ gal/yr transfer only, $200 \le x \le 1{,}800$ gal/yr				
both types, $140 \le x \le 1,800 \text{ gal/yr}$	both types, $140 \le x \le 1,800 \text{ gal/yr}$				
(constructed before 12/9/91)	(constructed on or after 12/9/91)				
5. Ineligible for General Permit drop store/out of business/petroleum					
facility exceeds above limits					
B. The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was gallons.					

PA	RT III: GENERAL CONTROL REQUIREMENTS - Rule 62-213.300 FAC	(check ☑ only one box			
Does the responsible official of the dry cleaning facility:			ich questi	ion)	
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes	□No	□N/A	
2.	Examine the containers for leakage?	⊠Yes	☐ No	□ N/A	
3.	Close and secure machine doors except during loading/unloading?	X Yes	☐ No		
4.	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes	□ No	□ N/A	
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes	□ No	⊠ N/A	
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the facility classification is a Existing small area source, no controls are requi	red. Pro	ceed to I	Part V.	
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993				
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped v	vith a ref	rigerated	
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	□No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	□No	□N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes	□No	□N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes	□No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- \[\text{Yes}	□No	⊠N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	□No		

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)					
1. Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No					
2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- □Yes □ No □N/A					
a) Is the temperature differential equal to, or greater than 20° F?	□Yes □ No □ N/A					
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A					
a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A					
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No □ N/A					
Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A					
6. Route airflow to the carbon adsorber (if used) at all times?	□Yes □ No □ N/A					
PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check ☑ only one box for					
Does the responsible official:	each question)					
1. Maintain receipts for perc purchased?	Yes 🛛 No					
2. Maintain rolling monthly total of yearly perc consumption?	☐ Yes ☒ No					
3. Maintain leak detection inspection and repair reports for the following:						
a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No N/A					
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No N/A					
4. Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No N/A					
5. Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ☐ N/A					
6. Maintain a startup/shutdown/malfunction plan?	⊠ Yes □ No					
7. Maintain deviation reports?						
l						
a) Problem corrected?	- ☐ Yes ☐ No ☒ N/A					
a) Problem corrected? 8. Maintain a compliance plan, if applicable?						

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check **☑** only one box for each question)

detection and repair inspection?				
2. Does the facility maintain a leak log?	Yes No			
3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves	Is			
4. Which method(s) of detection (is/are) used by the responsible official?				
a) Visual examination (condensed solvent on exterior surfaces) ————————————————————————————————————				
MARUFUL MALIK 01/21/2009				
Inspector's Name (Please Print)	Date of Inspection			
	01/10			
Inspector's Signature	Approximate Date of Next Inspection			

COMMENTS: On January 21, 2009 I visited this facility to conduct an annual compliance inspection. On site I met Jacoline Bermudez, the customer service personal. No leaks were detected in the dry cleaning machine. No records were avialable for PERC purchase and yearly PERC consumption,. No Halogen leak detector was available. An FNOV was issued for 1) No records 2) No leak detector.