

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/I		(CI) [
AIRS ID#: 0251050 DATI	E: <u>11/25/2013</u>	ARRIVE: <u>11:35</u>	<u>AM</u>	DEPART: <u>12:20PM</u>			
FACILITY NAME: ONE STOP DRY CLEANING							
FACILITY LOCATION:	2241 SW 22nd Street						
	MIAMI 33145						
OWNER/AUTHORIZED Email: dan.m.alvarez@ CONTACT NAME: ERI Email: ENTITLEMENT PERIOI	IC RODRIGUEZ		Mobile:	(305)285-8977 (817)808-0202 (305)860-1444			
PART I: INSPECTION COMPLIANCE STATUS (check ✓ only one box) ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE							
PART II: FACILITY CLASSIFICATION (check ✓ only one box in A) A. 1. Existing small area source ✓ 2. New small area source ✓							
dry-to-dry only, x both types, x < (constructed be 3. Existing large:	< 200 gal/yr 140 gal/yr fore 12/9/91)	dry-to-dry or transfer only both types, x (constructed 4. New large an	, x < 200 gal < 140 gal/yı on or after 1	/yr			
dry-to-dry only transfer only, 20 both types, 140 (constructed be 5. Ineligible for	$x \le 2,100 \text{ gal/yr}$ $00 \le x \le 1,800 \text{ gal/yr}$	dry-to-dry or	$ \begin{array}{lll} \text{nly, } 140 \le & x \\ \text{, } 200 \le & x \le \\ 40 \le & x \le \end{array} $				
B . The sum of the vo	lume of all perchloroethylene as 60.00 gallons.	(perc) purchases mad	e in each of	the previous 12 months by th	is dry		

PA	ART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC					only o		
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A	
2.	Are all perc. containers leak free ?		Yes		No		N/A	
3.	Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No			
4.	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	\boxtimes	Yes		No		N/A	
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No	\boxtimes	N/A	
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds							
	maintain according to the manufacturer's specifications?		Yes		No	\boxtimes	N/A	
PA	ART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC							
	efer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)							
	1. If the facility classification is an existing small area source, no controls are required. Proceed to Part V.							
2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.								
3. If the fa cility classification is an existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993								
4. If the facility classification is a <u>new large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.								
A.	Has the responsible official of all <u>existing large area & new sources</u> :					only o		
1.	Equipped all machines with the appropriate vent controls?		Yes		No			
2.						_		
	Equipped dry-to-dry machines with a closed-loop vapor venting system?	\boxtimes	Yes		No	Ш	N/A	
3.	Equipped dry-to-dry machines with a closed-loop vapor venting system? Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	\boxtimes	Yes		No No		N/A	
	Equipped the condenser with a diverter valve so airflow will be directed away	_	Yes					
4.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? Measured and recorded the temperature of the outlet exhaust stream of a	\boxtimes	Yes		No		N/A	

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
B. For all existing large or new large area sources:						
1. Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry,		Vac		N.		
reclaimer, and dryer machines measured and recorded on a weekly basis?	[Yes	Г	No		
2. Is the washer exhaus t temperature at the condenser inlet and outlet measured						
and recorded weekly?		Yes		No		N/A
a) Is the temperature differential equal to, or greater than 20° F?		Yes	□ N	No		N/A
3. Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber,						
if machines are equipped exclusively with a carbon adsorber?		Yes	\sqcap N	No	П	N/A
					_	
a) Is the perc concentration equal to, or less than 100 ppm?		Yes		No		N/A
4. Is the sampling port on the carbon adsorber exhaust for measuring						
perc concentrations at least 8 duct diameters downstream of any bend,						
contraction, or expansion; is at least 2 duct diameters upstream from any bend,						
contraction, or expansion; and downstream from no other inlet?	Ц	Yes	∐ N	No	Ш	N/A
5. Are transfer machines equipped (dryers, reclaimers, and washers) with individual						
condenser coils?		Yes	□ N	No		N/A
	_		_		_	
6. Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes	□ N	No		N/A
	_	Yes	□ N	No		N/A
	_	Yes	□ N	No		N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?	_					N/A
	_		(check	7 0	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?	_			7 0	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?			(check b	7 0	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?	\texts	bo	(check b ox for ea	✓ onech qu	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?	\texts	bo	(check b ox for ea	✓ onch qu	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?	\(\times \)	Yes Yes	(check b ox for ea	✓ onech qu	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?	\(\times \)	bo	(check Sox for ea	✓ onech qu	only only only only only only only only	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?	\(\times \)	yes Yes Yes	(check Sox for ea	✓ conch que	only of uestion	ne n) N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?	\(\times \)	Yes Yes	(check S in the content of the co	✓ conch que	only of uestion	ne n)
6. Is airflow routed to the carbon adsorber (if used) at all times?		yes Yes Yes	(check box for ea	✓ conch que No No No	only on its interest of the in	ne n) N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes Yes Yes	(check b ox for ea	✓ conch que No No No No	only on lestion	ne n) N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? 2. Are rolling monthly total s of yearly perc consumption maintained? 3. Are leak detection inspection and repair reports maintained for the following: a) Of any leaks repaired w/in 24 hrs? or; b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Is calibration data maintained for applicable direct reading instruments? 5. Is exhaust duct monitoring data on perc concentrations maintained?		Yes Yes Yes Yes Yes	(check Enterty for early f	✓ conch que No	only on lestion	ne n) N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes	(check be now for early and the now for earl	✓ conch que No	only on lestion	ne n) N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes Yes	(check box for ea	✓ conch que No	only on lestion	ne n) N/A N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes	(check box for ea	✓ conch que No	only on lestion	ne n) N/A N/A N/A

P	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		•	only one
1.	What type of leak detection equipment is used to detect leaks?	bo	ox for each	question)
	Halogenated hydrocarbon detector PCE gas analyzer None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ?	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery? $\ \ \ \ \ \ \ \ \ \ \ \ \ $	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes?	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn	nell or t	touch) whi	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection (of perceptib	ele leaks)
	b) Door gaskets and seating Yes No N/A h) Stills S		 No No No No No No	 N/A N/A N/A N/A N/A N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	enated	hydrocarb	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	graph sh	all satisfy ti	he
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers	Yes Yes Yes Yes Yes	NoNoNoNoNoNo	 N/A N/A N/A N/A N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)					
9. What evidence suggests that leak checks are performed as required? ☐ Leak log documentation ☐ RO Assurances ☐ On-site observation ☐ other Explain other:					
MARUFUL MALIK	11/25/2013				
Inspector's Name (Please Print)	Date of Inspection				
	11/2014				
Inspector's Signature	Approximate Date of Next Inspection				

COMMENTS: On November 25, 2013 I visited this facility to conduct the annual compliance inspection. On site I met Carlos Rodriguez, the manager of the facility. No leaks were detected in the Dry Cleaning Machine. Perc purchase receipts and yearly perc consumption records were available for the last calendar year. Halogen leak detector was available in working condition.

REVIEWED

By Ray Gordon at 10:33 am, Jan 28, 2014