

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/E		(CI)	
AIRS ID#: 0251058 DAT	ΓΕ: <u>8/19/2011</u>	ARRIVE: <u>10:15</u> A	<u>AM</u>	DEPART: <u>11:10AM</u>	
FACILITY NAME: ON	E LOW PRICE CLEANERS				
FACILITY LOCATION	: 14985 S Dixie Hwy				
	MIAMI 33176-7929				
OWNER/AUTHORIZEI Email: CONTACT NAME: Email: ENTITLEMENT PERIO	DREPRESENTATIVE: JULIO DD: 1/18/2007 / 1/18/2012 (effective date) (end date)	O ROSPIGLIOSI	PHONE: Mobile: PHONE: Mobile:	(305)378-8089	
PART I: INSPECTION IN COMPLIANCE	COMPLIANCE STATUS (che			Non-COMPLIANCE	
PART II: FACILITY CI	LASSIFICATION - Rule 62-2 only one box in A)	213.300 FAC			
transfer only, 3 both types, x < (constructed b 3. Existing large dry-to-dry onl transfer only, 3 both types, 14 (constructed b 5. Ineligible fo d rop store/out	y, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr pefore 12/9/91)		$\overline{\text{ly, x}} < 140 \text{ g}$ x < 200 gal/yr < 140 gal/yr on or after 12 rea source $\overline{\text{ly, 140}} \le x$ $200 \le x \le 40 \le x \le 40 \le x \le 40 \le x \le 40$	/yr 2/9/91) $x \le 2,100 \text{ gal/yr}$ 1,800 gal/yr 1,800 gal/yr	
B . The sum of the v cleaning facility v		perc) purchases mad	e in each of t	he previous 12 months by this dry	

PA	ART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC					only o	
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A
2.	Are all perc. containers leak free ?	\boxtimes	Yes		No		N/A
3.	Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No		
4.	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	\boxtimes	Yes		No		N/A
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No	\boxtimes	N/A
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds						
	maintain according to the manufacturer's specifications?		Yes		No	\boxtimes	N/A
PΛ	ART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC						
	efer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)						
	1. If the f acility classification is an <u>existing small area source</u> , no controls are required. P	roce	ed to P	art V	•		
	2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.						
	3. If the fa cility classification is an existing large area source , the machine should be equipped refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Compust have been installed prior to September 22, 1993</i>				a		
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refriş	gerate	d		
Α.	Has the responsible official of all <u>existing large area & new sources</u> :					only o	
1.	Equipped all machines with the appropriate vent controls?		Yes		No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	\boxtimes	Yes		No		N/A
3.			105	Ш	110	_	
	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?				No		N/A
4.	Equipped the condenser with a diverter valve so airflow will be directed away		Yes				
	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	\boxtimes	Yes		No		N/A

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
В.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes	1	No		
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?		Yes	_	No		N/A
	a) Is the temperature differential equal to, or greater than 20° F?	Ш	Yes		No	Ш	N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes	1	No		N/A
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes		No		N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes	1	No		N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes	1	No		N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	1	No		N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	1	No		N/A
	Is airflow routed to the carbon adsorber (if used) at all times?		(check E	√ o:	only o	ne
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		(check by for ea	√ o:	•	ne
P A			(bo	check E	✓ or	•	ne
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		(bo	check E	✓ onech qu	•	ne
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		(bo	check Ex for ea	✓ onech qu	•	ne
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		(bo Yes Yes	check Ex for each I	✓ onech qui	nestio	ne n)
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes	check Ex for each I	✓ o nch qu No No	iestio	ne n) N/A
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes	check Ex for each in the control of	v on on one of the one	iestio	ne n) N/A N/A
1. 2. 3. 4. 5.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes	check Ex for each of the control of	✓ onech qui No No No No	iestio	ne n) N/A N/A N/A
1. 2. 3. 4. 5. 6.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes	icheck Ex for each in the control of	✓ onech que No No No No No No No	iestio	ne n) N/A N/A N/A
1. 2. 3. 4. 5. 6. 7.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes	check Ex for each in the control of	vonch quach	S S S S S S S S S S S S S S S S S S S	ne n) N/A N/A N/A

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC (check ☑ only one						
1.	What type of leak detection equipment is used to detect leaks?	b	ox for each	question)		
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used					
2.	. Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to					
	the manufacturer's instructions (manual was available and RO could demonstrate					
	procedure) ?	Yes	☐ No			
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer					
	operated according to EPA Method 21 ?	Yes	☐ No	N/A		
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of					
	each component interface where leakage could occur and moving it slowly along					
	the interface periphery? $\ \ \ \ \ \ \ \ \ \ \ \ \ $	Yes	☐ No			
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or					
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per					
	million by volume (based on documented specifications) ? \cdots	Yes	☐ No	N/A		
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations					
	of PCE of 25 parts per million by volume (based on documented specifications) and					
	indicating a concentration of 25 parts per million by volume or greater by emitting					
	an audible or visual signal that varies as the concentration changes? $$	Yes	☐ No	N/A		
7.	Are the following dry cleaning system components inspected $\underline{\text{weekly}}$ for $\underline{\text{perceptible leaks}}$ (sight, sn	nell or	touch) whi	le the		
	system is in operation (§63.322(k))?					
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection of the properties	pection	of perceptib	le leaks)		
	b) Door gaskets and seating Yes No N/A h) Stills		No No No No No No	N/AN/AN/AN/AN/AN/A		
8.	Are the following dry cleaning system components inspected $\underline{monthly}$ for $\underline{vapor\ leaks}$ using a halog	enated	l hydrocarb	on detector		
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	graph s	hall satisfy th	ie		
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))					
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers	Yes Yes Yes Yes Yes	NoNoNoNoNoNoNo	N/AN/AN/AN/AN/AN/A		

PART VI: LEAK DETECTION AND REPAIRS - Rule 62	2-213.300 FAC (continued)
9. What evidence suggests that leak checks are performed as re ☐ Leak log documentation ☐ RO Assurances ☐ Explain other:	<u>_</u>
MARUFUL MAILK	8/19/2011
Inspector's Name (Please Print)	Date of Inspection
	8/19/2012
Inspector's Signature	Approximate Date of Next Inspection
GOLD FINITE	

COMMENTS: On August 19, 2011 I visited this facility to conduct the annual compliance inspection. On site I met Maria Sarcar, an attendant of the facility. No leaks were detected in the Dry Cleaning Machine. Halogen leak detector was available in working condition. An FNOV was issued for no perc purchased receipts.

REVIEWED

By Ray Gordon at 3:23 pm, Aug 22, 2011