

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

| <u>INSPECTION</u> <u>TYPE</u> : AN | NUAL (INS1, INS2) | COMPLAINT/DISCOVERY | (CI) | | |
|---|---|--|--|--|--|
| RE | -INSPECTION (FUI) | ARMS COMPLAINT NO: | | | |
| | | | | | |
| AIRS ID#: 0251059 DATE: <u>10/4/06</u> ARRIVE: <u>9:45 AM</u> DEPART: <u>10:40 AM</u> | | | | | |
| FACILITY NAME: RICHARD'S CLEANERS | | | | | |
| FACILITY LOCATION: 13607 SW 26th Street | | | | | |
| | MIAMI 33175 | | | | |
| RESPONSIBLE OFFICIAL | : KENNETH KOW | PHONE: (| 305)223-8676 | | |
| CONTACT NAME: | | PHONE: | | | |
| REMITTANCE YEAR: 2005 ENTITLEMENT PERIOD: 10/9/2003 / 10/9/2008 (effective date) (end date) | | | | | |
| | | | | | |
| PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) | | | | | |
| ☐ IN COMPLIANCE | MINOR Non-COMPI | LIANCE SIGNIFICANT 1 | Non-COMPLIANCE | | |
| | | | | | |
| PART II: <u>FACILITY CLAS</u> (check ✓ only on | | 3.300 FAC | | | |
| A. 1. Existing small are dry-to-dry only, x transfer only, x < 16 to types, x < 14 (constructed befor 3. Existing large are dry-to-dry only, 16 transfer only, 200 both types, 140 ≤ (constructed befor 5. Ineligible for Ger | < 140 gal/yr 200 gal/yr 0 gal/yr re 12/9/91) ea source | transfer only, x < 200 gal/y both types, x < 140 gal/yr (constructed on or after 12 4. New large area source dry-to-dry only, 140 ≤ x ≤ transfer only, 200 ≤ x ≤ 1,3 both types, 140 ≤ x ≤ 1,80 | dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91) | | |
| | ousiness/petroleum | | | | |
| B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 105 gallons. | | | | | |

| PA | RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC | (check ☑ only one box | | |
|-----------|---|--|--|--|
| Do | es the responsible official of the dry cleaning facility: | for each question) | | |
| 1. | Store perc, and wastes containing perc, in tightly sealed & impervious containers? | ⊠Yes □No □N/A | | |
| 2. | Examine the containers for leakage? | ⊠Yes □ No □ N/A | | |
| 3. | Close and secure machine doors except during loading/unloading? | ⊠ Yes □ No | | |
| | Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal? | ⊠Yes □ No □ N/A | | |
| 5. | Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications? | ☐Yes ☐ No ☒ N/A | | |
| | RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form) | | | |
| | 1. If the facility classification is a Existing small area source, no controls are requi | ired. Proceed to Part V. | | |
| | 2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below. | | | |
| | 3. If the facility classification is a Existing large area source , the machine should be refrigerated condenser or a carbon adsorber. Complete both sections A and B below <i>must have been installed prior to September 22, 1993</i> | | | |
| | 4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below. | quipped with a refrigerated | | |
| A. | Has the responsible official of all <u>existing large</u> <u>area</u> & <u>new sources</u> : | (check ☑ only one box for each question) | | |
| 1. | Equipped all machines with the appropriate vent controls? | ⊠Yes □No | | |
| 2. | Equipped dry-to-dry machines with a closed-loop vapor venting system? | Yes No N/A | | |
| 3. | Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? | Yes No N/A | | |
| 4. | Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis? | Yes No | | |
| 5. | Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F? | - □Yes □No ⊠N/A | | |
| 6. | Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged? | ⊠Yes □No | | |

| PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued) | | | | |
|--|---|--|--|--|
| B. Does the responsible official of an existing large or new large area source also: | (check ☑ only one box for each question) | | | |
| Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis? | □Yes □No | | | |
| 2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly? | - Yes No N/A | | | |
| a) Is the temperature differential equal to, or greater than 20° F? | □Yes □ No □ N/A | | | |
| 3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber? | □Yes □ No □ N/A | | | |
| a) Is the perc concentration equal to, or less than 100 ppm? | ☐Yes ☐ No ☐ N/A | | | |
| 4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet? | Yes No No | | | |
| 5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils? | - Yes No N/A | | | |
| 6. Route airflow to the carbon adsorber (if used) at all times? | □Yes □ No □ N/A | | | |
| | | | | |
| | | | | |
| PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC | | | | |
| Does the responsible official: | (check ✓ only one box for each question) | | | |
| 1. Maintain receipts for perc purchased? | - 🛚 Yes 🔲 No | | | |
| 2. Maintain rolling monthly total of yearly perc consumption? | ⊠ Yes □ No | | | |
| 3. Maintain leak detection inspection and repair reports for the following: | | | | |
| | | | | |
| a) documentation of leaks repaired w/in 24 hrs? or; | Yes No N/A | | | |
| a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? | - | | | |
| b) documentation of parts ordered to repair leak and leak repaired w/in 2 days | | | | |
| b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? | ☐ Yes ☐ No ☐ N/A ☐ Yes ☐ No ☐ N/A | | | |
| b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) | ☐ Yes ☐ No ☐ N/A ☐ Yes ☐ No ☐ N/A ☐ Yes ☐ No ☐ N/A | | | |
| b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations? | ☐ Yes ☐ No ☐ N/A ☐ Yes ☐ No ☐ N/A ☐ Yes ☐ No ☐ N/A ☐ Yes ☐ No | | | |
| b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations? 6. Maintain a startup/shutdown/malfunction plan? | ☐ Yes ☐ No ☐ N/A | | | |
| b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations? 6. Maintain a startup/shutdown/malfunction plan? | ☐ Yes ☐ No ☐ N/A ☐ Yes ☐ No ☐ N/A | | | |

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check \square only one box for each question)

| detection and repair inspection? | |
|--|-------------------------------------|
| 2. Does the facility maintain a leak log? | |
| d) Pumps | |
| 4. Which method(s) of detection (is/are) used by the responsible office a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric ture) Halogen leak detector **If using direct-reading instrumentation, is the equipment: 1) Capable of detecting perc vapor concentrations in a range of 0 2) Calibrated against a standard gas prior to and after each use (PI 3) Inspected for leaks and obvious signs of wear on a weekly basis 4) Kept in a clean and secure area when not in use? | a) |
| 5) Verified for accuracy by use of duplicate samples (calorimetric | |
| TERRENCE ANDERSON | 10/4/06 |
| Inspector's Name (Please Print) | Date of Inspection |
| | 10/07 |
| Inspector's Signature | Approximate Date of Next Inspection |
| COMMENTS: INSPECTION WAS PART OF THE DRY CLEANING STUDY LEAK DETECTED ,FNOV ISSUED. RECORDS AVAILABLE. AMIE DAVIS, MAISHA REED, WILBUR MYORGA, LISA SMITH INSPECTION. | H & LORNA BUCKNOR WAS PART OF THE |