

PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	
AIRS ID#: 0310504 DATE: <u>02/09/06</u> FACILITY NAME: OCEAN CLEANERS OF NE FACILITY LOCATION: 1505 Atlantic Bou	ilevard
NEPTUNE BEAC RESPONSIBLE OFFICIAL: JONG-TAE YOON	
CONTACT NAME:	PHONE:
REMITTANCE YEAR: 2005 EN	TITLEMENT PERIOD: 4/7/2001 / 4/7/2006 (effective date) (end date)
L	
PART I: INSPECTION COMPLIANCE STATE	US (check ☑ only one box) COMPLIANCE □ SIGNIFICANT Non-COMPLIANCE
PART II: FACILITY CLASSIFICATION - Rule (check  downly one box in A)         A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)         3. Existing large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr (constructed before 12/9/91)         5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits	<ul> <li>2. New small area source dry-to-dry only, x &lt; 140 gal/yr transfer only, x &lt; 200 gal/yr both types, x &lt; 140 gal/yr (constructed on or after 12/9/91)</li> <li>4. New large area source</li> </ul>

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box		
Does the responsible official of the dry cleaning facility:	for each question)		
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	∐Yes ∏No ⊠N/A		
2. Examine the containers for leakage?	Yes No N/A		
3. Close and secure machine doors except during loading/unloading?	Xes No		
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A		
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	Yes No N/A		

PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)						
<ol> <li>If the facility classification is a <u>Existing small area source</u>, no controls are required. Proceed to Part V.</li> </ol>						
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.					
3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> <i>Carbon adsorber must have been installed prior to September 22, 1993</i>						
	4. If the facility classification is a <u>New large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.					
А.	Has the responsible official of all <u>existing large area &amp; new sources</u> :		☑ only each que	one box for stion)		
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	No	□N/A		
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes	No	□N/A		
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes	No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	No	□N/A		
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	No			

	oes the responsible official of an existing large or new large area urce also:	(check ☑ only one box for each question)
	easure and record the exhaust temperature on the outlet side of the condenser cated on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No
	easure and record the washer exhaust temperature at the condenser let and outlet weekly?	- Yes No N/A
a)	Is the temperature differential equal to, or greater than $20^{\circ}$ F?	Yes No N/A
at	easure and record the perc concentration in the exhaust stream weekly the end of the final drying cycle while the machine is venting to the lsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A
a)	Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A
pe co	ssure that the sampling port on the carbon adsorber exhaust for measuring rc concentrations is at least 8 duct diameters downstream of any bend, ontraction, or expansion; is at least 2 duct diameters upstream from any bend, ontraction, or expansion; and downstream from no other inlet?	Yes No N/A
	uip transfer machines (dryers, reclaimers, and washers) with individual ndenser coils?	- Yes No N/A
6. Ro	pute airflow to the carbon adsorber (if used) at all times?	Yes No N/A

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC Does the responsible official:	(check ☑ only one box for each question)			
1. Maintain receipts for perc purchased?	- Xes No			
2. Maintain rolling monthly total of yearly perc consumption?	Yes No			
3. Maintain leak detection inspection and repair reports for the following:				
a) documentation of leaks repaired w/in 24 hrs? or;	- 🗌 Yes 🗌 No 🖾 N/A			
<ul> <li>b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?</li> </ul>	Yes No N/A			
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A			
5. Maintain exhaust duct monitoring data on perc concentrations?	Yes No N/A			
6. Maintain a startup/shutdown/malfunction plan?	- 🛛 Yes 🗌 No			
7. Maintain deviation reports?	- 🗌 Yes 🗌 No 🖾 N/A			
a) Problem corrected?	- Yes No N/A			
8. Maintain a compliance plan, if applicable?	- Yes No N/A			

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection? Xes No
2. Does the facility maintain a leak log? Xes I No
<ul> <li>3. Does the responsible official check the following areas for leaks?</li> <li>a) Hose connections, fittings, couplings, and valves</li> <li>b) Door gaskets and seating</li> <li>c) Filter gaskets and seating</li> <li>d) Pumps</li> <li>e) Solvent tanks and containers</li> <li>f) Water separators</li> <li>Yes □No □N/A</li> </ul>
<ul> <li>4. Which method(s) of detection (is/are) used by the responsible official?</li> <li>a) Visual examination (condensed solvent on exterior surfaces) a) </li> <li>b) Physical detection (airflow felt through gaskets) b) </li> <li>c) Odor (noticeable perc odor) c) </li> <li>d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) d) </li> <li>e) Halogen leak detector e) </li> </ul>
<ul> <li>**If using direct-reading instrumentation, is the equipment:</li></ul>
WILLIAM COFFMAN 2/9/06

Inspector's Name (Please Print)

Date of Inspection

1/9/07

Inspector's Signature

Approximate Date of Next Inspection

COMMENTS: