

## HALOGENATED SOLVENT DEGREASERS



## COMPLIANCE INSPECTION CHECKLIST

| INSPECTION TYPE:  | ANNUAL (INS1, INS2)<br>RE-INSPECTION (FUI)            | COMPLAINT/DISCOVE   | · , —                     |  |  |  |
|---|---|---------------------|---------------------------|--|--|--|
| AIRS ID#: 1030481 DA  | ΓΕ: <u>6/9/08</u>                                     | ARRIVE: 9:40 a.m.   | DEPART: <u>11:15 a.m.</u> |  |  |  |
| FACILITY NAME: UN   | ILENS CORP, USA                                       |                     |                           |  |  |  |
| FACILITY LOCATION   | : 10431 72nd Street N                                 | North               |                           |  |  |  |
|   | LARGO 33777-1   | 511                 |                           |  |  |  |
| OWNER/AUTHORIZEI  | D REPRESENTATIVE:                                     | MICHAEL PECORA PHON | <b>IE:</b> (727)544-2531  |  |  |  |
| CONTACT NAME: M   | ichael Pecora   | PHON                | Œ:                        |  |  |  |
| ENTITLEMENT PERIO   | <b>DD:</b> 2/6/2006 / 2/6/20 (effective date) (end da |                     |                           |  |  |  |
| PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box)  ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE  |   |                     |                           |  |  |  |
| PART II: NOTIFICATION – Rule 62-210.300 FAC (check ☑ appropriate box(es))  1. Halogenated solvent used at facility: perchloroethylene ☐ following machine type(s).  methylene chloride ☐ Batch Vapor, x ≤ 1.21 m² ☐ Batch Vapor, x > 1.21 m² ☐ Sexisting In-line ☐ Existing In-line ☐ Batch Cold |   |                     |                           |  |  |  |
|   |   |                     | Batch Cold (immersion)    |  |  |  |

|    | RT IV: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC A. Batch Vapor and In-Line Machines  |        |          |      |
|----|--|--------|----------|------|
|    | 1. Does the facility maintain an idling and downtime mode cover that is readily opened and closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?        | ⊠Yes   | □No      |      |
|    | 2. Does the facility maintain a freeboard ratio of 0.75 or greater?  | ⊠Yes   | □No      |      |
|    | 3. Does the facility utilize a parts basket or parts whose size is less than 50% of the solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?  | - ⊠Yes | □No      |      |
|    | 4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?   | □Yes   | □No      |      |
|    | 5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?  | Yes    | □No      |      |
|    | 6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorbe should not be by-passed, the lip exhaust shall be located above the closed machine cover  |        | □No      | ⊠N/A |
|    | 7. Does the facility have each machine equipped with:  a. a device to shut off sump heat if the solvent level drops to the heater coils?  b. a device to shut off sump heat if the vapor level rises above the height of the   | ⊠Yes   | □No      |      |
|    | vapor condenser?c. a primary condenser?  | ⊠Yse   | ∐N<br>□N |      |
|    | 8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?  | ⊠Yes   | □No      |      |
| В. | Batch Cold Cleaning Machines  1. Does the facility collect and store all waste solvent in closed containers?  2. Does the facility use a flexible hose or flushing device only within the  | ⊠Yes   | □No      |      |
|    | freeboard area?  |        | □No      |      |
|    |  |        | □No      |      |
|    | the fill line?5. Does the facility immediately clean up spills during solvent transfer?  | - XYes | □No      |      |
|    | Store wipe rags in a covered container?  6. Does the facility operate the agitator to produce a rolling motion? (applicable  | ⊠Yes   | □No      |      |
|    | only when air or pump agitated solvent bath used) 7. Does the facility ensure that the machine is not exposed to drafts greater than   | Yes    | □No      | ⊠N/A |
|    | 40 m/min (132 ft/min) when the cover is open?  | ⊠Yes   | □No      |      |
|    | 8. Does the facility ensure that sponges, fabrics, wood and paper products are <u>not</u> placed in the machine?   | ⊠Yes   | □No      |      |
|    | <ul> <li>Remote Reservoir Type Only</li> <li>9. Does the facility employ a tightly fitting cover over the solvent sump?</li> <li>The cover must be closed at all times except during parts cleaning</li> <li>Immersion Type Only</li> </ul>  | ⊠Yes   | □No      | □N/A |
|    | 10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio of 0.75? Tightly fitting cover must be closed at all times except during parts entry and removal. | ⊠Yes   | □No      | □N/A |
|    | ·· · · · · · · · · · · · · · · · · · ·   |        |          |      |

| PA | PART V: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (not applicable to batch cold cleaning machines)  Facility chose to meet requirements using:  control device combination / work practice standards |  |  |  |  |  |  |  |
|----|--|--|--|--|--|--|--|--|
| A. | Batch Vapor  | Machines, $x \le 1.21 \text{ m}^2$   |  |  |  |  |  |  |
|    | (Select control combination)   |  | <u>DEVICE IN USE</u>   |  |  |  |  |  |
|    | 1.  □g 2.  □g 3.  □g 4.  □g 5.  □g 6.  □g 7.  □g 8.  □g  | working mode cover reduced room draft reduced room draft freeboard refrig. device          | 1.0 freeboard ratio - \[ \] 1.0 freeboard ratio - \[ \] 1.0 freeboard ratio - \[ \] superheated vapor \[ \] working mode cover \[ \] reduced room draft 1.0 freeboard ratio - \[ \] dwell \[ \]  | superheated vapor superheated vapor dwell  |  |  |  |  |
|    | 9.   | freeboard refrig. device arbon adsorber  | carbon adsorber 1.0 freeboard ratio -  | superheated vapor  |  |  |  |  |
| В. | Batch Vapor  | Machines, $x > 1.21 \text{ m}^2$   |  |  |  |  |  |  |
|    | ( Select contro  | ol   |  |  |  |  |  |  |
|    | combination  |  | <u>DEVICE</u> <u>IN</u> <u>USE</u>   |  |  |  |  |  |
|    | <ol> <li>□g</li> </ol>   | freeboard refrig. device freeboard ratio | superheated vapor Superheated vapor Superheated vapor Superheated vapor Feduced room draft - Feduced r | 1.0 freeboard ratio   working mode cover   reduced room draft   carbon adsorber   dwell    1.0 freeboard ratio   superheated vapor |  |  |  |  |
| C. | Existing In-I  | Line Machines  |  |  |  |  |  |  |
|    | (Select control combination)   |  | <u>DEVICE IN USE</u>   |  |  |  |  |  |
|    | 1.   | freeboard refrig. device superheated vapor freeboard refrig. device carbon adsorber  | 1.0 freeboard ratio -  |  |  |  |  |  |
| D. | New In-Line  | Machines   |  |  |  |  |  |  |
|    | (Select control combination)   |  | <u>DEVICE IN USE</u>   |  |  |  |  |  |
|    |  | freeboard refrig. device freeboard refrig. device superheated vapor  | superheated vapor - carbon adsorber carbon adsorber  |  |  |  |  |  |

| PART VI: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC  |            |       |   |  |  |  |
|--|------------|-------|---|--|--|--|
| <u>Has the responsible official maintained the following:</u>  |            |       |   |  |  |  |
| 1. Owner's manuals, design specifications, and other instructional materials for cleaning machine and control equipment? |            | No    | □N/A □N/A □N/A □N/A □N/A □N/A □N/A □N/A |  |  |  |
| Jeff Morris 6/6/08   |            |       |   |  |  |  |
| Inspector's Name (Please Print)  Date of Inspection  |            |       |   |  |  |  |
| Inspector's Signature Approximate Date of Next   | Inspection | <br>1 |   |  |  |  |
| <b>COMMENTS:</b> Highest usage = 23 kg/mo (Aug, 07')   |            |       |   |  |  |  |
| 23 kg/mo / 0.163 sf area = 141 kg/square meter/month less than 150 kg/square meter/month                                 |            |       |   |  |  |  |
| The facility qualifies for the alternative standard.   |            |       |   |  |  |  |
| Alternative standard:  |            |       |   |  |  |  |
| Area of the tank not exceed 150 kg/square meter/month for batch vapor solvent cleaning machines.                         |            |       |   |  |  |  |