

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2	COMPLAINT/DISCOVERY (CI)						
RE-INSPECTION (FU	I) ARMS COMPLAINT NO:						
AIRS ID#: 0951256 DATE: <u>8/16/2007</u>	ARRIVE: <u>10:30</u> DEPART: <u>11:15</u>						
FACILITY NAME: SOUTHSIDE \$1.50 CLEANERS							
FACILITY LOCATION: 11570 S Orange Blossom Tr #15							
ORLANDO 32	837						
RESPONSIBLE OFFICIAL: ASHLEY FREEM	IAN PHONE: (407)438-2980						
CONTACT NAME:	PHONE:						
REMITTANCE YEAR: 2005 E.	NTITLEMENT PERIOD: 7/29/2004 / 7/29/2009 (effective date) (end date)						
PART I: INSPECTION COMPLIANCE STAT							
IN COMPLIANCE MINOR Nor	-COMPLIANCE SIGNIFICANT Non-COMPLIANCE						
PART II: FACILITY CLASSIFICATION - Ru (check ☑ only one box in A)	ıle 62-213.300 FAC						
A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91) 3. Existing large area source	 2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91) 4. New large area source 						
dry-to-dry only, $140 \le x \le 2,100$ gal/y transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before $12/9/91$)							
5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits							
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 220 gallons.							

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box					
Does the responsible official of the dry cleaning facility:			for each question)				
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes	□No	□N/A			
2.	Examine the containers for leakage?	⊠Yes	☐ No	□ N/A			
3.	Close and secure machine doors except during loading/unloading?	X Yes	☐ No				
4.	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes	□ No	□ N/A			
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes	□No	⊠ N/A			
	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form)						
	1. If the facility classification is a Existing small area source, no controls are requi	red. Pro	ceed to I	Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.						
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993						
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped v	vith a ref	rigerated			
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)					
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	□No				
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	□No	□N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes	□No	□N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes	□No				
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	□No	⊠N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	□No				

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)							
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)					
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No					
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?						
	a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☐ No ☒ N/A					
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ☑ N/A					
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☒ N/A					
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No ⊠ N/A					
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- □Yes □ No □ N/A					
6.	Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☒ N/A					
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC							
	bes the responsible official:	(check ☑ only one box for each question)					
1.	Maintain receipts for perc purchased?	⊠ Yes □ No					
2.	Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No					
3.	Maintain leak detection inspection and repair reports for the following:						
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A					
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No N/A					
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☐ N/A					
5.	Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ☐ N/A					
6.	Maintain a startup/shutdown/malfunction plan?	Yes No					
7.	Maintain deviation reports?						
	a) Problem corrected?	Yes No N/A					
8.	Maintain a compliance plan, if applicable?	☐ Yes ☐ No N/A					

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	X Yes No				
2. Does the facility maintain a leak log?3. Does the responsible official check the following areas for leaks?					
a) Hose connections, fittings, couplings, and valves	ookers Yes No N/A Yes No N/A dampers Yes No N/A valves Yes No N/A ge filter housings Yes No N/A				
4. Which method(s) of detection (is/are) used by the responsible official?					
a) Visual examination (condensed solvent on exterior surfaces)					
**If using direct-reading instrumentation, is the equipment:					
Assefa Hailemariam 8/16/2007					
Inspector's Name (Please Print)	Date of Inspection				
~8/	/16/2008				
Inspector's Signature	Approximate Date of Next Inspection				
COMMENTS: Please Purchase ahalogen leak detector for the perc. and use once amonth. thank you.					