WHERE PROTECTION	
State Deserve	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/D ARMS COMPL	DISCOVERY (CI)						
AIRS ID#: 0112610 DATE: <u>11/29/2011</u>	ARRIVE: <u>1430</u>	DEPART: <u>1500</u>						
FACILITY NAME: NEIGHBOURHOOD CLEANERS	FACILITY NAME: NEIGHBOURHOOD CLEANERS							
FACILITY LOCATION: 1421 NW 47TH AVE								
LAUDERHILL 33321-5	5547							
Email: CONTACT NAME: Email:	OWNER/AUTHORIZED REPRESENTATIVE:JOSEPH GORDONPHONE:(954)735-1039Email:Mobile:CONTACT NAME:PHONE:Email:Mobile:Email:Mobile:ENTITLEMENT PERIOD:10/15/2007 / 10/15/2012							
	PART I: INSPECTION COMPLIANCE STATUS (check I only one box) □ IN COMPLIANCE □ MINOR Non-COMPLIANCE □ IN COMPLIANCE □ SIGNIFICANT Non-COMPLIANCE							
PART II: FACILITY CLASSIFICATION (check \square only one box in A) - Rule 62-213.300 FAC A.1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91) C New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr								

cleaning facility was 20.00 gallons.

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC		```	check ☑ x for each c	only one question)
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes	🗌 No	N/A
2. Are all perc. containers leak free ?	\boxtimes	Yes	🗌 No	N/A
3. Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes	🗌 No	
 Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal? 		Yes	🗌 No	N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with				
manufacturer's instructions		Yes	🗌 No	N/A
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes	🗌 No	N/A

PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)
1. If the f acility classification is an existing small area source, no controls are required. Proceed to Part V.
2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.
3. If the fa cility classification is an <u>existing large area source</u> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i>

4.	If the fa	cility classificatio	n is a <u>nev</u>	7 <mark>large area so</mark>	ource, the	machine s	should be ea	quipped wi	th a refrigera	ited
col	ndenser.	Complete both s	ections A	and B below.						

A	. Has the responsible official of all <u>existing large area & new sources</u> :		`	check ☑ x for each c	only one question)
1.	Equipped all machines with the appropriate vent controls?	\boxtimes	Yes	🗌 No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	\boxtimes	Yes	🗌 No	N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	\boxtimes	Yes	🗌 No	N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	\boxtimes	Yes	🗌 No	□ N/A
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	\boxtimes	Yes	🗌 No	□ N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	\boxtimes	Yes	🗌 No	

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)			
B. 1.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?	Yes	🗌 No	
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly? a) Is the temperature differential equal to, or greater than 20° F?	Yes Yes	D No	□ N/A □ N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes	🗌 No	N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes	🗌 No	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes	🗌 No	□ N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?	Yes	🗌 No	N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?	Yes	🗌 No	N/A

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		(chec box for		only one question)
1. Are receipts maintained for all perc purchased?	Y	es 🗌	No	
2. Are rolling monthly total s of yearly perc consumption maintained ?	Y	'es	No	
3. Are leak detection inspection and repair reports maintained for the following:				
a) Of any leaks repaired w/in 24 hrs? or;] Y	es	No	N/A
b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?] Y	'es	No	N/A
4. Is calibration data maintained for applicable direct reading instruments? \sum	Y	es 🗌	No	N/A
5. Is exhaust duct monitoring data on perc concentrations maintained?	Y	es 🗌	No	N/A
6. Is a startup/shutdown/malfunction plan maintained for each machine?	Y	es	No	
7. Are deviation reports maintained?	Y	es 🗌	No	N/A
a) Problem corrected?] Y	'es 🗌	No	N/A
8. Is a compliance plan maintained, if applicable?] Y	es	No	N/A

P	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	(check	only one
1.	What type of leak detection equipment is used to detect leaks?		ach question)
	Halogenated hydrocarbon detector PCE gas analyzer None used		
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to		
	the manufacturer's instructions (manual was available and RO could demonstrate		
	procedure) ? 🖂	Yes 🗌 I	No
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer		
	operated according to EPA Method 21 ?	Yes 🗌 I	No 🛛 N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of		
	each component interface where leakage could occur and moving it slowly along		
	the interface periphery?	Yes 🗌 I	No
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or		
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per		
	million by volume (based on documented specifications) ?	Yes 🗌 I	No 🗌 N/A
6.	Is the halogenated hydrocarbon detector capable of detecting vapor concentrations		
	of PCE of 25 parts per million by volume (based on documented specifications) and		
	indicating a concentration of 25 parts per million by volume or greater by emitting		
	an audible or visual signal that varies as the concentration changes? $\hfill \hfill $	Yes 🗌 I	No 🗌 N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn	mell or touch)	while the
	system is in operation (§63.322(k))?		
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection of perce	ptible leaks)
	b) Door gaskets and seating Yes No N/A h) Stills X c) Filter gaskets and seating Yes No N/A i) Exhaust dampers X d) Pumps Yes No N/A j) Diverter valves Y	Yes N Yes N Yes N Yes N Yes N	o 🗌 N/A o 🔲 N/A o 🔲 N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	genated hydroc	arbon detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parage	graph shall sati	sfy the
	requirements to conduct an inspection for perceptible leaks under $63.322(k)$ or (l)		
	b) Door gaskets and seating Xes No N/A N) Stills c) Filter gaskets and seating Xes No N/A i) Exhaust dampers	Yes N Yes N Yes N Yes N Yes N Yes N	o 🗌 N/A o 🔲 N/A o 🔲 N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)							
 9. What evidence suggests that leak checks are performed as required? Leak log documentation RO Assurances On-site observation other Explain other : 							
Elizabeth F.Susky	11/29/2011						
Inspector's Name (Please Print)	Date of Inspection						
	11/29/2012						
Inspector's Signature	Approximate Date of Next Inspection						
COMMENTS: In a compliance inspection conducted on 11/29/2011, AQD staff (E.Susky) observed operations at Neighborhood dry-cleaners. The owner was not present during the inspection. The facility has one PERC dry-cleaner. The spotting board area had metal plating beneath it. The dry-cleaning calendar was not observed to be present. The REMA							

vacuum had recently been replaced, but was not properly contained. AQD staff did not observe the drums of hazardous waste on-site, they will need to be stored in a visible area