

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVERY ARMS COMPLAINT NO:	(CI)	
AIRS ID#: 1170391 DA	ATE: <u>04/25/07</u>	ARRIVE: <u>09:36am</u>	DEPART: <u>11:45am</u>	
FACILITY NAME: FI	FACILITY NAME: FIFTH AVENUE CLEANERS			
FACILITY LOCATION	FACILITY LOCATION: 801 W S. R. 436 Ste 1001			
	ALTAMONTE SPRINC	GS 32714		
RESPONSIBLE OFFIC	RESPONSIBLE OFFICIAL: JOSEPH BRAY PHONE:			
CONTACT NAME: PHONE:				
REMITTANCE YEAR	: 2005 ENTITL	EMENT PERIOD: 8/27/2005 (effective date)	/ 8/27/2010 (end date)	
IN COMPLIAN	NCE X MINOR Non-COMF		Non-COMPLIANCE	
	CLASSIFICATION - Rule 62-2 nly one box in A)	13.300 FAC		
transfer only both types, x	all area source nly, x < 140 gal/yr y, x < 200 gal/yr x < 140 gal/yr before 12/9/91)	2. <u>New small area source</u> dry-to-dry only, x < 140 g transfer only, x < 200 gal/ both types, x < 140 gal/yr (constructed on or after 12	/yr	
transfer only both types, 1	ge area source nly, $140 \le x \le 2,100$ gal/yr y, $200 \le x \le 1,800$ gal/yr $40 \le x \le 1,800$ gal/yr before 12/9/91)	4. New large area source dry-to-dry only, $140 \le x \le$ transfer only, $200 \le x \le 1$, both types, $140 \le x \le 1.80$ (constructed on or after 12)	,800 gal/yr 00 gal/yr	
drop store/ou	r General Permit ut of business/petroleum eds above limits			
	ity of perchloroethylene (perc) put was 400 gallons.	rchased within the preceding 12 m	onths by this dry	

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	□Yes ⊠No □N/A
2. Examine the containers for leakage?	□Yes ⊠ No □ N/A
3. Close and secure machine doors except during loading/unloading?	Yes No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	∐Yes ∏No ⊠N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No □ N/A

PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form)					
	1. If the facility classification is a Existing small area source , no controls are required. Proceed to Part V.				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.				
А.	Has the responsible official of all <u>existing large area & new sources</u> : (check d only one box for each question)				
1.	Equipped all machines with the appropriate vent controls? XYes				
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system? XYes No				
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?				
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?				
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F? XYes No N/A				
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged? XYes No				

PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)			
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)	
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No	
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?		
	a) Is the temperature differential equal to, or greater than 20° F?	Yes No N/A	
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A	
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A	
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A	
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A	
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A	

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC Does the responsible official:	(check ☑ only one box for each question)
1. Maintain receipts for perc purchased?	- 🛛 Yes 🗌 No
2. Maintain rolling monthly total of yearly perc consumption?	🗌 Yes 🖾 No
3. Maintain leak detection inspection and repair reports for the following:	
a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No N/A
 b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 	□ Yes □ No □ N/A
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A
5. Maintain exhaust duct monitoring data on perc concentrations?	Yes No N/A
6. Maintain a startup/shutdown/malfunction plan?	Yes 🗌 No
7. Maintain deviation reports?	Yes No N/A
a) Problem corrected?	- 🗌 Yes 🗌 No 🖾 N/A
8. Maintain a compliance plan, if applicable?	Yes No N/A

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?
2. Does the facility maintain a leak log? 🗌 Yes 🖾 No
 3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves □Yes □No N/A g) Muck cookers □Yes □No N/A b) Door gaskets and seating □Yes □No N/A h) Stills □Yes □No N/A c) Filter gaskets and seating □Yes □No N/A i) Exhaust dampers □Yes □No N/A d) Pumps □Yes □No N/A j) Diverter valves □Yes □No N/A e) Solvent tanks and containers □Yes □No N/A f) Water separators
4. Which method(s) of detection (is/are) used by the responsible official?
 a) Visual examination (condensed solvent on exterior surfaces) a) b) Physical detection (airflow felt through gaskets) b) c) Odor (noticeable perc odor) c) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) d) e) Halogen leak detector e)
 **If using direct-reading instrumentation, is the equipment:

Ferman Fletcher

Inspector's Name (Please Print)

04/25/2007

Date of Inspection

04/24/2008

Inspector's Signature

Approximate Date of Next Inspection

COMMENTS: Open containers of muck from still Floor around machine should be resealed Containers of waste not labeled Must clean of much around machine Maintain emergency information by telephones Conduct waste container inspections Maintain leak log