

CHROMIUM ELECTROPLATING/ANODIZING



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INSPECTION) RE-INSPECTION		
AIRS ID#: 0251143 DATE: <u>10/23/07</u>	ARRIVE: 10:45am DEPART: 11:30am	
FACILITY NAME: PERKO INC		
FACILITY LOCATION: 16490 NW 13th Avenue		
MIAMI 33169-5718		
RESPONSIBLE OFFICIAL: FRED PE	PHONE: (305)621-7525	
CONTACT NAME: MORTE CLARK	PHONE:	
REMITTANCE YEAR: 2006	ENTITLEMENT PERIOD: 9/11/2003 / 9/11/2008 (effective date) (end date)	
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE		
PART II: CLASSIFICATION – Rule 62-213.300 FAC Facility type(s)/applicable standard as indicated on notification form:		
Hard Chromium Plating a. Existing Large (0.015 mg/dscm c. New (0.015 mg/dscm)		
2. <u>Decorative Chromium Plating/Anodizing</u>		
a. <u>Chromic Acid Bath</u>	 Emissions of ≤ 0.01/mg/dscm (4.4x10⁻⁶ gr/dscf) Surface tension of ≤ 45 dynes/cm (3.1x10⁻³ lb-f/ft) (May only be selected if a wetting agent is used.) 	
b. Trivalent Chromium Bath	1) With wetting agent	
c. <u>Chromium</u> <u>Anodizing</u>	 Emissions of ≤ 0.01 mg/dscm (4.4x10⁻⁶ gr/dscf) Surface tension of 45 dynes/cm (3.1x10⁻³ lb-f/ft) (May only be selected if a wetting agent is used.) 	

PART III: CONTROL TECHNOLOGY - Rule 62-213.300 FAC	
(Salact control	
(<u>Select control</u> device)	DEVICE IN USE?
<u>device</u>)	DEVICE IN USE:
1. Composite Mesh Pad	∏Yes ∏No
2. Fiber Bed Mist Eliminator	Yes No
3. Packed Bed Scrubber	Yes No
4. Packed Bed Scrubber/Composite Mesh Pad	Yes No
5. Foam Blanket Fume Suppressant	Yes No
6. Eume Suppressant w/ Wetting Agent	⊠Yes □No
Has the facility conducted an initial performance test to establish monitoring parameters? (Not required for sources using a wetting agent or 1-inch foam blanket thickness)	☐Yes ☐No ☐N/A
PART IV: <u>RECORDKEEPING/REPORTING REQUIREMENTS</u> – Rule 62-213.300	(3)
Has the responsible official maintained the following records?	
1. Quarterly inspection records for add-on air pollution control devices and	
monitoring equipment. (applicable only to a facility using a packed bed scrubber	, fiber-bed
mist eliminator, or composite mesh pad)	Yes No N/A
2. Operations and Maintenance Plan (OMP). (applicable only to a facility using a	packed bed
scrubber, fiber-bed mist eliminator, or composite mesh pad)	Yes No N/A
3. Maintenance records for the source, add-on pollution control devices, and	
monitoring equipment (equipment identified, date performed, description)	- □Yes □No
4. Records of date of occurrence, duration, cause, and corrective action of each	
malfunction of process, add-on pollution control device, and monitoring equipmen	it. Yes No
5. Results of all performance tests	
6. Records of monitoring data. (not applicable to trivalent chromium baths using	
agent)	Yes No No N/A
Composite Mesh Pad	
Measure the pressure drop across the CMP daily	- ∐Yes ∐No
Packed Bed Scrubber	
Measure the pressure drop across the PBS and the inlet velocity daily.	☐Yes ☐No
Fiber-Bed Mist Eliminator	DV DN-
Measure the pressure drop across the FBME and the upstream device daily	☐Yes ☐No
Packed Bed Scrubber/Composite Mesh Pad Massayan the pressure drop cores the CMP doily	
Measure the pressure drop across the CMP daily	∐Yes ∐No
Foam Blanket Fume Suppressant Measure the foam blanket thickness at the appropriate interval	□Yes □No
Fume Suppressant w/ Wetting Agent	
Measure the surface tension at the appropriate interval	⊠Yes □No
7. Purchase records of wetting agent components.	
8. Records of the date and time that fume suppressants are added to the bath	
9. Records of rectifier capacity, if used to determine facility size	
10. Records of the total process operating time	
11. Records identifying specific periods of excess emissions	
12. Startup, Shutdown & Malfunction Plan	

MARQUES LOPEZ	10/23/07	
Inspector's Name (Please Print)	Date of Inspection	
	10/08	
Inspector's Signature	Approximate Date of Next Inspection	

COMMENTS: ON October 23, 2007 FRANK DELGADO AND I VISITED THIS FACILITY TO CONDUCT THE ANNUAL COMPLIANCE INSPECTION. ON SITE WE MET MORTE CLARK THE CHEMICAL PROCESS MANAGER. HE SHOWED US THE THREE CHROMIUM TANKS WHICH HAD WETTING AGENT APPLIED TO SUPPRESS EMMISSIONS. THE SURFACE TENSION WITH IN THE TANKS ARE KEPT AT A LEVEL OF 33 DYNE/CM2 WHICH IS WELL BELOW THE MAXIMAL ALLOWABLE LIMIT OF 45.