

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVER	RY (CI)	
1	RE-INSPECTION (FUI)	ARMS COMPLAINT NO	:	
AIRS ID#: 1030499 DAT	E: <u>1/15/09</u>	ARRIVE: <u>10:15 a.m.</u>	DEPART: <u>10:45 a.m.</u>	
FACILITY NAME: \$1.99	CLEANERS			
FACILITY LOCATION:	3390 E BAY DR			
	LARGO 33771-6900			
OWNER/AUTHORIZED	REPRESENTATIVE: SUI	OHIR PATEL PHONE	: (727)536-2845	
CONTACT NAME:		PHONE	:	
ENTITLEMENT PERIO	D: 8/31/2008 / 8/31/2013 (effective date)	3		
	COMPLIANCE STATUS (c	· —		
	E MINOR Non-COMI	PLIANCE	T Non-COMPLIANCE	
PART II: <u>FACILITY CL</u> (check ☑ only	ASSIFICATION - Rule 62-2 one box in A)	213.300 FAC		
A. 1. Existing small dry-to-dry only transfer only, x both types, x < (constructed be	/, x < 140 gal/yr < < 200 gal/yr 140 gal/yr	2. New small area source dry-to-dry only, x < 140 transfer only, x < 200 g both types, x < 140 gal/ (constructed on or after	D gal/yr al/yr ⁄yr	
transfer only, 2	x , $140 \le x \le 2,100$ gal/yr $100 \le x \le 1,800$ gal/yr $10 \le x \le 1,800$ gal/yr	4. New large area source dry-to-dry only, $140 \le x$ transfer only, $200 \le x \le$ both types, $140 \le x \le 1$ (constructed on or after	x \(\leq 2,100\) gal/yr (1,800\) gal/yr (800\) gal/yr	
	Cananal Dawnit			
5. Ineligible for (drop store/out of facility exceeds	of business/petroleum			

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box				
Does the responsible official of the dry cleaning facility:		for each question)				
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A				
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A				
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No				
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A				
5.	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No □ N/A				
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)					
	1. If the facility classification is a Existing small area source, no controls are requi	ired. Proceed to Part V.				
	2. If the facility classification is a <u>New small area source</u> , the machine should be econdenser. Complete section A. below.	quipped with a refrigerated				
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993					
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped with a refrigerated				
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)				
1.	Equipped all machines with the appropriate vent controls?	Yes No				
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	- ⊠Yes □No □N/A				
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	- ⊠Yes □No □N/A				
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	- ⊠Yes □No				
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- ⊠Yes □No □N/A				
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No				

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)	
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A
	a) Is the temperature differential equal to, or greater than $20^{\rm o}$ F?	☐Yes ☐ No ☒ N/A
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ⊠ N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☒ N/A
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	· □Yes □ No □ N/A
5	Equip transfer machines (dryers, reclaimers, and washers) with individual	
٥.	condenser coils?	Yes No N/A
6.	Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☒ N/A
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check ☑ only one box for
Do	es the responsible official:	each question)
1.	Maintain receipts for perc purchased?	- 🛚 Yes 🔲 No
2.	Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No
3.	Maintain leak detection inspection and repair reports for the following:	
	a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No No N/A
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No N/A
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☐ N/A
5.	Maintain exhaust duct monitoring data on perc concentrations?	Yes No No N/A
6.	Maintain a startup/shutdown/malfunction plan?	Yes No
7.	Maintain deviation reports?	Yes No N/A
l	Manual de Mation reports.	
	a) Problem corrected?	

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?						
3. Does the responsible official check the following areas for leaks?						
a) Hose connections, fittings, couplings, and valves						
4. Which method(s) of detection (is/are) used by the responsible official?						
a) Visual examination (condensed solvent on exterior surfaces) ————————————————————————————————————						
Jeff Morris 1/16/09						
Inspector's Name (Please Print) Date of Inspection						
1/16/10						
Inspector's Signature Approximate Date of Next Inspection						

COMMENTS: Based on an annual inspection, the facility has failed to use a halogenated leak detector that has been a requirement for existing area source dry cleaners since July 28, 2008.