CONNECTION PROTECTION	
Same Mana	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISC ARMS COMPLAIN					
AIRS ID#: 0112664 DATE: <u>9/24/2012</u>	ARRIVE: <u>1200</u>	DEPART: <u>140</u>				
FACILITY NAME: ONE PRICE DRY CLEANING						
FACILITY LOCATION: 12387 PEMBROKE RD						
PEMBROKE PINES 33	025-1723					
OWNER/AUTHORIZED REPRESENTATIVE: KISH Email: kishorb1234@hotmail.com CONTACT NAME: KISHOR BHAKM Email: kishorb1234@hotmail.com ENTITLEMENT PERIOD: 1/20/2012 / 1/20/2017 (effective date) (end date)	M Pl	HONE: (404)587-8989 [obile: (934)437-6574 HONE: (404)587-8989 [obile: (934)437-6574				
l <u> </u>						
	PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) □ IN COMPLIANCE □ SIGNIFICANT Non-COMPLIANCE					
ir						
PART II: FACILITY CLASSIFICATION (check ☑ only one box in A) - Rule 62-213.300 FAC A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr 2. New small area source dry-to-dry only, x < 140 gal/yr						
transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)	transfer only, x < both types, x < 1 (constructed on c	40 gal/yr or after 12/9/91)				
 3. Existing large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr (constructed before 12/9/91) 5. Ineligible for General Permit 	transfer only, 20	$\begin{array}{rrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrr$				
5. Ineligible for General Permit d rop store/out of business/petroleum / facility exceeds above limits						

B. The sum of the volume of all perchloroethylene (perc) purchases made in each of the previous 12 months by this dry cleaning facility was gallons.

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC			check ☑ x for each c	only one juestion)
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes	🗌 No	N/A
2. Are all perc. containers leak free ?	\boxtimes	Yes	🗌 No	N/A
3. Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes	🗌 No	
 Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal? 	\boxtimes	Yes	🗌 No	N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes	□ No	X N/A
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds		103		
maintain according to the manufacturer's specifications?	\boxtimes	Yes	🗌 No	N/A

	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC							
(R	(Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)							
	1. If the facility classification is an existing small area source, no controls are required. Proceed to Part V.							
	2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.							
	3. If the fa cility classification is an <u>existing large area source</u> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993							
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.							
A.	. Has the responsible official of all existing large area & new sources: (check 🗹 only one box for each question)							
1.	Equipped all machines with the appropriate vent controls? Xes Ves No							
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system? 🛛 Yes 🗌 No 🗌 N/A							
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? X Yes No N/A							
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis? Yes No N/A							
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F? Ves No X/A							

6.	Conducted all temperature monitoring after an appropriate cool-down period and			
	after verifying that the coolant had been completely charged?	Yes	\boxtimes	No

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)			
B. 1.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?	Yes	🗌 No	
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly? a) Is the temperature differential equal to, or greater than 20° F?	Yes Yes	D No	⊠ N/A ⊠ N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes	🗌 No	N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes	🗌 No	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes	🗌 No	N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?	Yes	🗌 No	N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?	Yes	🗌 No	N/A

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(chec box for		only one uestion)
1. Are receipts maintained for all perc purchased?	Yes 🖂	No	
2. Are rolling monthly total s of yearly perc consumption maintained ?	Yes 🛛	No	
3. Are leak detection inspection and repair reports maintained for the following:			
a) Of any leaks repaired w/in 24 hrs? or;	Yes	No	N/A
b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes 🗌	No	N/A
4. Is calibration data maintained for applicable direct reading instruments?	Yes	No	N/A
5. Is exhaust duct monitoring data on perc concentrations maintained?	Yes	No	N/A
6. Is a startup/shutdown/malfunction plan maintained for each machine? 🖂	Yes	No	
7. Are deviation reports maintained?	Yes	No	N/A
a) Problem corrected?	Yes	No	N/A
8. Is a compliance plan maintained , if applicable?	Yes 🗌	No	N/A

PA	ART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC	((check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?		ox for each	•
	Halogenated hydrocarbon detector PCE gas analyzer None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ? 🖂	Yes	🗌 No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	🗌 No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery? 🕅	Yes	🗌 No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	🗌 No	N/A
6.	Is the halogenated hydrocarbon detector capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes? $\hfill \hfill $	Yes	🗌 No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sr	mell or	touch) whi	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection	of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills c) Filter gaskets and seating Yes No N/A i) Exhaust dampers d) Pumps Yes No N/A j) Diverter valves	Yes Yes Yes Yes Yes	 No No No No No No No 	 □ N/A □ N/A □ N/A □ N/A □ N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	genated	hydrocarb	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parage	graph sh	all satisfy th	ne
	requirements to conduct an inspection for perceptible leaks under $63.322(k)$ or (l)			
	b) Door gaskets and seating Yes No N/A h) Stills c) Filter gaskets and seating Yes No N/A i) Exhaust dampers d) Pumps Yes No N/A j) Diverter valves	Yes Yes Yes Yes Yes	 No No No No No No No 	□ N/A □ N/A □ N/A □ N/A □ N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62	2-213.300 FAC (continued)					
 9. What evidence suggests that leak checks are performed as required? Leak log documentation RO Assurances On-site observation other Explain other : None maintained 						
Cynthia Fernandez	9/24/2012					
Inspector's Name (Please Print)	Date of Inspection					
	October 24, 2012					
Inspector's Signature Approximate Date of Next Inspection						
COMMENTS: Not in compliance. RO did not provide caler days.	ndar and PERC receipts. Will conduct f/u to verify con	mpliance in 30				