

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOVE ARMS COMPLAINT NO	, , , <u>—</u>			
AIRS ID#: 0251229 DA	ΓΕ: <u>8/9/2011</u>	ARRIVE: 10:55AM	DEPART: <u>11:35AM</u>			
FACILITY NAME: WHITE LINEN DRY CLEANERS LLC						
FACILITY LOCATION	8044 NW 90 ST					
	MEDLEY 33166-2114					
OWNER/AUTHORIZEI Email: CONTACT NAME: Email: ENTITLEMENT PERIC	DREPRESENTATIVE: ANT DD: 12/6/2007 / 12/6/2012 (effective date) (end date)	ONIO RODRIGUEZ PHONI Mobile: PHONI Mobile:	: E:			
PART I: <u>INSPECTION</u> ☑ IN COMPLIANO	COMPLIANCE STATUS (che		NT Non-COMPLIANCE			
A. 1. Existing small dry-to-dry onl	l area source y, x < 140 gal/yr x < 200 gal/yr	213.300 FAC 2. New small area source dry-to-dry only, x < 14 transfer only, x < 200 g both types, x < 140 gal	10 gal/yr gal/yr			
(constructed b 3. Existing large dry-to-dry onl transfer only, both types, 14 (constructed b 5. Ineligible for d rop store/ou	pefore 12/9/91)	constructed on or afte 4. New large area source dry-to-dry only, 140 \le transfer only, 200 \le z both types, 140 \le x \le (constructed on or afte)	r 12/9/91) e			
	volume of all perchloroethylene (was 80.00 gallons.	perc) purchases made in each	of the previous 12 months by this dry			

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC			check 🗹	only one question)
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes	☐ No	N/A
2. Are all perc. containers leak free ?	\boxtimes	Yes	☐ No	□ N/A
3. Are all machine doors kept closed and secured except during loading/unloading?		Yes	☐ No	
4. Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	\boxtimes	Yes	☐ No	□ N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes	☐ No	⊠ N/A
Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes	☐ No	N/A
PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form) 1. If the f acility classification is an existing small area source, no controls are required. I	Proce	ed to P	art V.	
2. If the facility classification is a <u>new small area source</u> , the machine should be equipped condenser. Complete section A. below.	with	a refrig	gerated	
3. If the fa cility classification is an <u>existing large area source</u> , the machine should be equ refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Must have been installed prior to September 22, 1993</i>				
4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refriş	gerated	
A. Has the responsible official of all existing large area & new sources:			check 2 ox for each	
1. Equipped all machines with the appropriate vent controls?		Yes	☐ No	
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?	\boxtimes	Yes	☐ No	□ N/A
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	\boxtimes	Yes	☐ No	□ N/A
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	\boxtimes	Yes	☐ No	□ N/A
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?		Yes	☐ No	N/A
6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?		Yes	☐ No	

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
B. For all existing large or new large area sources:						
1. Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry,						
reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes		No		
2. Is the washer exhaus t temperature at the condenser inlet and outlet measured						
and recorded weekly?		Yes		No		N/A
a) Is the temperature differential equal to, or greater than 20° F?		Yes		No		N/A
3. Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber,						
if machines are equipped exclusively with a carbon adsorber?		Yes		No		N/A
		37. .		NT.		37/4
a) Is the perc concentration equal to, or less than 100 ppm?	Ц	Yes	Ш	No	Ш	N/A
4. Is the sampling port on the carbon adsorber exhaust for measuring						
perc concentrations at least 8 duct diameters downstream of any bend,						
contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes		No		N/A
Contraction, or expansion, and downstream from no other finee.		105		110		14/11
5. Are transfer machines equipped (dryers, reclaimers, and washers) with individual					_	
ll						
condenser coils?		Yes		No		N/A
	_	Yes Yes		No No		N/A N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?	_					
	_					
6. Is airflow routed to the carbon adsorber (if used) at all times?	_					
	_	Yes	(check	No	only o	N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes		No	-	N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes	(check	No	-	N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes	(check ox for e	No Zeach o	-	N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes bo Yes	(check ox for e	No And the search of the sear	-	N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?	\(\times \)	yes bo Yes Yes	(check ox for e	No each o	questio	N/A one on)
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————	\(\times \)	Yes bo Yes	(check ox for e	No And the search of the sear	-	N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?	\(\times \)	yes bo Yes Yes	(check ox for e	No each o	questio	N/A one on)
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————	\(\times \)	yes Yes Yes Yes Yes	(check ox for e	No No No No	questio	N/A one on N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? 2. Are rolling monthly total s of yearly perc consumption maintained? 3. Are leak detection inspection and repair reports maintained for the following: a) Of any leaks repaired w/in 24 hrs? or; b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Is calibration data maintained for applicable direct reading instruments?		yes yes Yes Yes Yes Yes Yes	(check	No No No No No No	questio	N/A one on) N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No No No No No No No No	questio	N/A one on N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No	questio	N/A one on N/A N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213,300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No N	question	N/A one on) N/A N/A N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? ————————————————————————————————————		yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No	question	N/A one on N/A N/A N/A N/A

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC			(check ☑ only o		
1.	1. What type of leak detection equipment is used to detect leaks?			question)	
	Halogenated hydrocarbon detector PCE gas analyzer None used				
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to				
	the manufacturer's instructions (manual was available and RO could demonstrate				
	procedure) ?	Yes	☐ No		
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer				
	operated according to EPA Method 21 ?	Yes	☐ No	N/A	
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of				
	each component interface where leakage could occur and moving it slowly along				
	the interface periphery? $\ \ \ \ \ \ \ \ \ \ \ \ \ $	Yes	☐ No		
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or				
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per				
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A	
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations				
	of PCE of 25 parts per million by volume (based on documented specifications) and				
	indicating a concentration of 25 parts per million by volume or greater by emitting				
	an audible or visual signal that varies as the concentration changes?	Yes	☐ No	N/A	
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn	nell or t	touch) whi	le the	
	system is in operation (§63.322(k))?				
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection (of perceptib	ele leaks)	
	b) Door gaskets and seating Yes No N/A h) Stills S		 No No No No No No	 N/A N/A N/A N/A N/A N/A 	
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	enated	hydrocarb	on detector	
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	graph sh	all satisfy ti	he	
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))				
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers	Yes Yes Yes Yes Yes	NoNoNoNoNoNo	 N/A N/A N/A N/A N/A 	

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.3	300 FAC (continued)			
9. What evidence suggests that leak checks are performed as required? ☐ Leak log documentation ☐ RO Assurances ☐ On-site observation ☐ other Explain other:				
MARUFUL MALIK	8/9/2011			
Inspector's Name (Please Print)	Date of Inspection			
	8/9/2012			
Inspector's Signature	Approximate Date of Next Inspection			

COMMENTS: On August 09, 2011 I visited this facility to conduct the annual compliance inspection. On site I met Juan Cruz, the manager of the facility. No leaks were detected in the Dry Cleaning Machine. Perc purchase receipts and yearly perc consumption records were available. Halogen leak detector was available in working condition.