

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVER	RY (CI)			
	RE-INSPECTION (FUI)	ARMS COMPLAINT NO				
AIRS ID#: 0970085 DA	TE: <u>6/26/08</u>	ARRIVE: <u>2:25 pm</u>	DEPART: 3:08 pm			
FACILITY NAME: S&B DRYCLEANER INC						
FACILITY LOCATION: 3063 Michigan avenue						
	KISSIMMEE 34744-1501					
OWNER/AUTHORIZE	D REPRESENTATIVE: SHA	AMEE UMARALLY PHONE	: (407)348-4000			
CONTACT NAME: Pa	am Umarally	PHONE	:			
ENTITLEMENT PERIOD: 9/21/2006 / 9/21/2011 (effective date) (end date)						
DADEL INCRECTION						
IN COMPLIANCE	CE MINOR Non COM	·	IT Non COMPLIANCE			
☐ IN COMPLIANC	CE MINOR Non-COMI	PLIANCE SIGNIFICAN	T Non-COMPLIANCE			
	<u>CLASSIFICATION</u> - Rule 62-2 ly one box in A)	213.300 FAC				
transfer only, both types, x	ly, x < 140 gal/yr x < 200 gal/yr	2. New small area source dry-to-dry only, x < 140 transfer only, x < 200 g both types, x < 140 gal/ (constructed on or after	gal/yr al/yr yr			
transfer only, both types, 14	e area source \square ly, $140 \le x \le 2,100 \text{ gal/yr}$ $200 \le x \le 1,800 \text{ gal/yr}$ $40 \le x \le 1,800 \text{ gal/yr}$ before $12/9/91)$	4. New large area source dry-to-dry only, $140 \le x$ transfer only, $200 \le x \le$ both types, $140 \le x \le 1$ (constructed on or after	x ≤ 2,100 gal/yr 1,800 gal/yr 800 gal/yr			
drop store/out	t of business/petroleum ds above limits					
B . The total quantity cleaning facility		archased within the preceding 12	months by this dry			

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box	
Do	es the responsible official of the dry cleaning facility:	for each question)	
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A	
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A	
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No	
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A	
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No ⊠ N/A	
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)		
	1. If the facility classification is a Existing small area source, no controls are requi	ired. Proceed to Part V.	
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.		
	3. If the facility classification is a Existing large area source , the machine should be refrigerated condenser or a carbon adsorber. Complete both sections A and B belo <i>must have been installed prior to September 22, 1993</i>		
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped with a refrigerated	
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)	
1.	Equipped all machines with the appropriate vent controls?	⊠Yes □No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes □No	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- Yes No N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No	

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)					
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)			
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No			
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No No			
	a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☐ No ☐ N/A			
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A			
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A			
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No □ N/A			
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No No			
6.	Route airflow to the carbon adsorber (if used) at all times?	□Yes □ No □ N/A			
	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC best he responsible official:	(check ☑ only one box for each question)			
1.	Maintain receipts for perc purchased?	Yes No			
2.	Maintain rolling monthly total of yearly perc consumption?	☐ Yes ☒ No			
3.	Maintain leak detection inspection and repair reports for the following:				
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A			
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No N/A			
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No N/A			
5.	Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No N/A			
6.	Maintain a startup/shutdown/malfunction plan?	⊠ Yes □ No			
7.	Maintain deviation reports?	Yes No N/A			
	a) Problem corrected?	Yes No N/A			
8.	Maintain a compliance plan, if applicable?	Yes No N/A			

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Yes No			
2. Does the facility maintain a leak log?				
3. Does the responsible official check the following areas for leaks a) Hose connections, fittings, couplings, and valves	Muck cookers Yes No N/A Stills Yes No N/A Exhaust dampers Yes No N/A Diverter valves Yes No N/A			
4. Which method(s) of detection (is/are) used by the responsible official? a) Visual examination (condensed solvent on exterior surfaces)				
**If using direct-reading instrumentation, is the equipment: — ** N/A 1) Capable of detecting perc vapor concentrations in a range of 0-500 ppm? — 1) Yes No 2) Calibrated against a standard gas prior to and after each use (PID/FID only)? — 2) Yes No 3) Inspected for leaks and obvious signs of wear on a weekly basis? — 3) Yes No 4) Kept in a clean and secure area when not in use? — 4) Yes No 5) Verified for accuracy by use of duplicate samples (calorimetric only)? — 5) Yes No				
Rodell Rice	2/04/08			
Inspector's Name (Please Print)	Date of Inspection			
	2/2009			
Inspector's Signature	Approximate Date of Next Inspection			
COMMENTS:				