

04/13/2007 23:51 8634526293
 Jul. 9. 2009 11:35AM FLORIDA TIRE SUPPLY

FTT

PAGE 01/02

No.3413 P. 1

ATTEN.
 RAQUEL ARIAS

Material Safety Data Sheet
E844 Black Tire Paint™ Concentrate

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is sold or otherwise distributed with intention of earning profit thereon.

MANUFACTURER AND COMPANY IDENTIFICATION

Stoner Incorporated
 1070 Robert Fulton Hwy.
 Quarryville, PA 17566
 1-800-227-5538

Product Name: Black Tire Paint™ Concentrate
 Product Code: E844
 Version Date: 02/06/09
 24-hour emergency phone: 1-800-424-9300 (CITEMTREC)

COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS #	ACGIH TLV	OSHA PEL	OTHER
Water	7732-18-9	Not established	Not established	Not established
Organic coating	MIXTURE	Not established	Not established	Not established
Color dispersion	1333-86-4	Not established	Not established	Not established
Ester Alcohol	25265-77-4	Not established	Not established	Not established
NJ Trade Secret Registry	#80100382-3094P	400 ppm	400 ppm	Not established
Nonionic surfactant	9016-45-9	Not established	Not established	Not established

HAZARD IDENTIFICATION

POTENTIAL ACUTE (single or short term) HEALTH EFFECTS OF OVEREXPOSURE
 Eye: May cause eye irritation. Symptoms may include redness, tearing, and redness.
 Skin: Skin contact may cause irritation. Symptoms may include redness, discomfort, drying and cracking, or melt. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.
 Ingestion: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.
 Inhalation: Inhalation can cause nose, throat, and respiratory tract irritation, coughing and headache. Inhalation may cause irritation of the upper respiratory passages. Breathing small amounts during handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache.

POTENTIAL CHRONIC (long term) HEALTH EFFECTS OF OVEREXPOSURE:
 General Effects: Upon prolonged or repeated use, can be associated with central nervous system damage. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: mild, reversible kidney effects, mild, reversible liver effects, skin sensitization.

Cancer Information: THIS PRODUCT CONTAINS NO COMPONENTS LISTED AS CARCINOGENIC BY IARC, NTP, OR OSHA 1910(Z)
 Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:
 No medical conditions affected by exposure. Unlikely to aggravate existing medical conditions. No data found.

HMSD III* HAZARDOUS WARNINGS:

Health: 1 Flammability: 1 Physical: 0 Personal Protective Equipment: See Section 8
 * See www.p201.org/html or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

SAFETY AND MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse.
Ingestion: Do not induce vomiting. Have victim drink 8 to 16 ounces of water to dilute the material in the stomach. Contact a physician, medical facility, or poison control center immediately. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Aspiration into the lungs can cause serious damage.
Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep the victim warm and quiet. Seek immediate medical attention.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions);

FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: Material can splatter above 212F. Dried product can burn. "Rinse" contains retain product residue and can be dangerous.
Fire Fighting Instructions: Use CO2, foam or dry chemical. Do not direct a solid stream of water or foam into hot burning pools, this may cause frothing and increase fire intensity.
Flash Point: None* PMCC
Lower Flammability Limit: No data available
Upper Flammability Limit: No data available
Autoignition Temperature: No data available

FAX
 JUL 09 2009
RECEIVED

From Bill
 Florida Tire Terminal

04/13/2007 23:51

8634526293

FTT

PAGE 02/02

Jul. 9. 2009 11:36AM

FLORIDA TIRE SUPPLY

No.3413 P. 2

IDENTIFICATION

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLS:

Wear appropriate personal protective equipment (PPE). Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. If runoff occurs, notify authorities as required. Remove all sources of ignition. Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container.

HAZARD

Handling: Use with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Wash hands thoroughly after handling.
Storage: Keep container tightly closed when not in use. Keep from freezing. Store in a cool, dry, well ventilated area away from all sources of ignition. Normal precautions common to safe manufacturing practice should be followed in handling and storage.

EXPOSURE LIMITS

Engineering Controls: No exposure limits exist for the constituents of this product. General room ventilation might be required to maintain operator comfort under normal conditions of use. Ventilation should be adequate to prevent exposures above the limits indicated in "Section 2" of this MSDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded.
Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Do not wear contact lenses. Have an eye wash station available.
Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection: Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Black liquid	Vapor Density:	(air = 1) 1.78
Appearance:	Black	Evaporation Rate:	0.1-0.5 (n-Butyl acetate = 1)
Odor:	Acrylic	Solubility in Water:	Complex; 100%
Specific Gravity:	1.07 (H2O=1)	Boiling Point:	212°F
Vapor Pressure:	36 PSIG @ 70°F	pH:	Not applicable

STABILITY

Chemical Stability: Stable.
Conditions to Avoid: Avoid contact with: Strong oxidizing agents. Reducing agents.
Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Acrylic Polymer. Oxides of sulfur.

DISPOSAL

Disposal: Dispose according to Federal, State and local regulations.

TRANSPORTATION

Agency	Proper Shipping name	UN Number	Hazard Class	Packing Group
DOT	Not regulated by agency	1		
IATA	Not regulated by agency			

REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:
COMPONENT **CAS #** **% BY WEIGHT** **Regulatory Body**
No components listed in this section. **SARA Section 313**

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.			
1,4 Dioxane	123-91-1	0.0001 - 0.0001	Prop65 Cancer
Ethylene oxide	75-21-8	0.0001 - 0.0001	Prop65 Cancer
Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.			
Ethylene oxide	75-21-8	0.0001 - 0.0001	Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.

