OWERTAL WOTECTION
San Martin
FLORIDA

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOVER	Y (CI)
AIRS ID#: 0251330 DATE: <u>3/5/2014</u>	ARRIVE: <u>11:02 AM</u>	DEPART: <u>11:30 AM</u>
FACILITY NAME: CLEAN-ESS-PRO LLC		
FACILITY LOCATION: 1181 SE 9th TERRACE		
HIALIAH 33010		
OWNER/AUTHORIZED REPRESENTATIVE: ALEJ Email: Cleanesspro@yahoo.com CONTACT NAME: LISETTE MONTES Email: Cleanesspro@yahoo.com ENTITLEMENT PERIOD: 12/19/2010 / 12/19/201 (effective date) (end date)	Mobile: PHONE: Mobile:	(954)663-2869 (954)701-5980 (954)663-2869 (954)701-5980
l <u></u>		
PART I: INSPECTION COMPLIANCE STATUS (che		T Non-COMPLIANCE
PART II: FACILITY CLASSIFICATION (check I only one box in A) - Rule 62-2	213.300 FAC	
A. 1. Existing small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91)3. Existing large area source \Box dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)5. Ineligible for General Permit \Box d rop store/out of business/petroleum / facility exceeds above limits	 2. New small area source dry-to-dry only, x < 140 transfer only, x < 200 gal both types, x < 140 gal/y (constructed on or after 1 4. New large area source dry-to-dry only, 140 ≤ transfer only, 200 ≤ x ≤ both types, 140 ≤ x ≤ (constructed on or after 1 	ll/yr /r 12/9/91) ⊥ x ≤ 2,100 gal/yr ≤ 1,800 gal/yr 1,800 gal/yr

B. The sum of the volume of all perchloroethylene (perc) purchases made in each of the previous 12 months by this dry cleaning facility was 0.00 gallons.

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	-		check x for e		only c questio		
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?		Yes		No	\boxtimes	N/A	
2. Are all perc. containers leak free ?		Yes		No	\boxtimes	N/A	
3. Are all machine doors kept closed and secured except during loading/unloading?		Yes		No			
 Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?		Yes		No	\boxtimes	N/A	
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No		N/A	
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes		No	\boxtimes	N/A	
DADTINA BRACESS VENT CONTROLS Dula 62 212 200 FAC							
PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)							
1. If the f acility classification is an existing small area source , no controls are required. P	rocee	d to P	art V.	•			
2. If the facility classification is a <u>new small area source</u> , the machine should be equipped we condenser. Complete section A. below.	with a	ı refrig	erated	l			
3. If the fa cility classification is an existing large area source , the machine should be equip refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Compute have been installed prior to September 22, 1993</i>				ì			
4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refrig	gerated	1			
A. Has the responsible official of all existing large area & new sources: (check ☑ only one box for each question)							
1. Equipped all machines with the appropriate vent controls?		Yes		No			
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?		Yes		No	\boxtimes	N/A	
3. Equipped the condenser with a diverter valve so airflow will be directed away		Yes		No	\boxtimes	N/A	
from the condenser upon opening the door?							
 from the condenser upon opening the door? 4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis? 		Yes		No	\boxtimes	N/A	
4. Measured and recorded the temperature of the outlet exhaust stream of a		Yes Yes	_	No No	\boxtimes	N/A N/A	

PA	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
B. 1.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes	🗌 No			
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly? a) Is the temperature differential equal to, or greater than 20° F?		Yes Yes	D No	⊠ N/A ⊠ N/A		
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes	🗌 No	N/A		
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes	🗌 No	N/A		
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes	🗌 No	N/A		
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes	🗌 No	N/A		
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	🗌 No	N/A		

PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	`	check ☑ x for each q	only one [uestion]
1.	Are receipts maintained for all perc purchased?	Yes	D No	
2.	Are rolling monthly total s of yearly perc consumption maintained ?	Yes	🗌 No	
3.	Are leak detection inspection and repair reports maintained for the following:			
	a) Of any leaks repaired w/in 24 hrs? or;	Yes	🗌 No	N/A
	b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes	🗌 No	N/A
4.	Is calibration data maintained for applicable direct reading instruments?	Yes	🗌 No	N/A
5.	Is exhaust duct monitoring data on perc concentrations maintained?	Yes	🗌 No	N/A
6.	Is a startup/shutdown/malfunction plan maintained for each machine?	Yes	🗌 No	
7.	Are deviation reports maintained?	Yes	🗌 No	N/A
	a) Problem corrected?	Yes	🗌 No	N/A
8.	Is a compliance plan maintained , if applicable?	Yes	🗌 No	N/A

P	ART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC	(check 🗹 only one
1.	What type of leak detection equipment is used to detect leaks?	box for each question)
	Halogenated hydrocarbon detector PCE gas analyzer None used	
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to	
	the manufacturer's instructions (manual was available and RO could demonstrate	
	procedure) ?	Yes 🗌 No
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer	
	operated according to EPA Method 21 ?	Yes Do No A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of	
	each component interface where leakage could occur and moving it slowly along	
	the interface periphery?	Yes 🗌 No
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or	
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per	
	million by volume (based on documented specifications) ?	Yes 🗌 No 🖾 N/A
6.	Is the halogenated hydrocarbon detector capable of detecting vapor concentrations	
	of PCE of 25 parts per million by volume (based on documented specifications) and	
	indicating a concentration of 25 parts per million by volume or greater by emitting	
	an audible or visual signal that varies as the concentration changes?	Yes Do N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn	nell or touch) while the
	system is in operation (§63.322(k))?	
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	vection of perceptible leaks)
	b) Door gaskets and seating Yes No N/A h) Stills C) c) Filter gaskets and seating Yes No N/A i) Exhaust dampers C) d) Pumps Yes No N/A j) Diverter valves Yes	YesNoN/AYesNoN/AYesNoN/AYesNoN/AYesNoN/AYesNoN/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	enated hydrocarbon detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	graph shall satisfy the
	requirements to conduct an inspection for perceptible leaks under $63.322(k)$ or (l)	
	b) Door gaskets and seating Yes No N/A h) Stills C) c) Filter gaskets and seating Yes No N/A i) Exhaust dampers d) Pumps Yes No N/A j) Diverter valves Yes	Yes No N/A Yes No N/A Yes No N/A Yes No N/A Yes No N/A Yes No N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)							
 9. What evidence suggests that leak checks are performed as required? Leak log documentation RO Assurances On-site observation other Explain other : 							
FRANK DELGADO	3/5/2014						
Inspector's Name (Please Print)	Date of Inspection 3/2015	_					

Inspector's Signature

Approximate Date of Next Inspection

COMMENTS: MR. MONTES APPLIED FOR THE REGISTRATION CERTIFICATE TO BUY PERC IN FEBRUARY 2014. HE IS PLANNING TO START USING THE DRY CLEANING MACHINE SOON.

REVIEWED By Ray Gordon at 12:21 pm, Mar 12, 2014