## Dibble, Dickson

From: March, Marta (DERM) [marchm@miamidade.gov]

Sent: Monday, April 27, 2009 2:17 PM

To: Dibble, Dickson

Cc: Gordon, Ray (DERM)

Subject: Please remove from ARMS - Doral Golf Resort & Spa

Dick,

As per the last inspection conducted at this facility on February 21, 2008, this facility no longer works as a dry cleaner. Please update ARMS accordingly. Thank you.

ARMS # 0251089

Facility Name: DORAL GOLF RESORT & SPA

Facility Address: 4400 NW 87TH AVE, MIAMI - 33178-2101

Marta March, Engineer! Air Facilities Section Department of Environmental Resources Management (DERM) Tel: (305) 372-6929 Fax: (305) 372-6954 www.miamidade.gov/DERM "Delivering Excellence Every Day"

Miami-Dade County is a public entity subject to Chapter 119 of the Florida Statutes concerning public records.

E-mail messages are covered under such laws and thus subject to disclosure.

3:15PM- 4 30 09

MARTA WILL GET BACK

MACHINE 7

MACHINE 7



## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2)	COMPLAINT/DISCOVERY (CI)			
RE-INSPECTION (FUI)	ARMS COMPLAINT NO:			
AIRS ID#: 0251089 DATE: <u>2/21/08</u>	ARRIVE: <u>12:42pm</u> DEPART: <u>12:59pm</u>			
FACILITY NAME: DORAL GOLF RESORT & SPA				
FACILITY LOCATION: 4400 NW 87TH AVE				
MIAMI 33178-2101				
OWNER/AUTHORIZED REPRESENTATIVE: LAZ	ZARO RAXACH PHONE: (305)592-2000			
CONTACT NAME:	PHONE:			
<b>ENTITLEMENT PERIOD:</b> 3/26/2007 / 3/26/2012				
(effective date) (end date)				
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box)				
☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE				
PART II: FACILITY CLASSIFICATION - Rule 62-213.300 FAC				
(check only one box in A)				
A. 1. Existing small area source  dry-to-dry only, x < 140 gal/yr  transfer only, x < 200 gal/yr  both types, x < 140 gal/yr  (constructed before 12/9/91)	2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91)			
3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before $12/9/91$ )	4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after $12/9/91$ )			
5. Ineligible for General Permit  drop store/out of business/petroleum facility exceeds above limits				
B. The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was gallons.				

PA	ART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check only one box		
Does the responsible official of the dry cleaning facility:  for each question)				
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	□Yes □No □N/A		
2.	Examine the containers for leakage?	☐Yes ☐ No ☐ N/A		
3.	Close and secure machine doors except during loading/unloading?	☐ Yes ☐ No		
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	□Yes □ No □ N/A		
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No □ N/A		
PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form)  1. If the facility classification is a Existing small area source, no controls are required. Proceed to Part V.  2. If the facility classification is a New small area source, the machine should be equipped with a refrigerated condenser. Complete section A. below.  3. If the facility classification is a Existing large area source, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993  4. If the facility classification is a New large area source, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.				
<b>A.</b>	Has the responsible official of all <u>existing large</u> <u>area</u> & <u>new sources</u> :	(check ☑ only one box for each question)		
1.	Equipped all machines with the appropriate vent controls?	- · · · · · · · · · · · · · · · · · · ·		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	- □Yes □No □N/A		
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	- Yes No N/A		
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	- Yes No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- Yes No N/A		
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	. TYes TNo		

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)	
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No
Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- []Yes [] No []N/A
a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☐ No ☐ N/A
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A
a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No □ N/A
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A
6. Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☐ N/A
PARTY, RECORDIZERNIC REQUIREMENTS, P.J. (2.212.2002) EAC	
PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC  Does the responsible official:	(check ☑ only one box for each question)
1. Maintain receipts for perc purchased?	Yes No
2. Maintain rolling monthly total of yearly perc consumption?	☐ Yes ☐ No
3. Maintain leak detection inspection and repair reports for the following:	
a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No ☐ N/A
4. Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☐ N/A
5. Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ☐ N/A
6. Maintain a startup/shutdown/malfunction plan?	
Maintain a startup/shutdown/malfunction plan?      Maintain deviation reports?	Yes No
	☐ Yes ☐ No ☐ Yes ☐ No ☐ N/A
7. Maintain deviation reports?	<ul> <li>☐ Yes</li> <li>☐ No</li> <li>☐ Yes</li> <li>☐ No</li> <li>☐ N/A</li> </ul>

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Yes No
2. Does the facility maintain a leak log?	Yes No
c) Filter gaskets and seating d) Pumps	rck cookers
4. Which method(s) of detection (is/are) used by the responsible offici  a) Visual examination (condensed solvent on exterior surfaces)  b) Physical detection (airflow felt through gaskets)  c) Odor (noticeable perc odor)  d) Use of direct-reading instrumentation (FID/PID/calorimetric tube) Halogen leak detector  **If using direct-reading instrumentation, is the equipment:  1) Capable of detecting perc vapor concentrations in a range of 0-5  2) Calibrated against a standard gas prior to and after each use (PII 3) Inspected for leaks and obvious signs of wear on a weekly basis 4) Kept in a clean and secure area when not in use?  5) Verified for accuracy by use of duplicate samples (calorimetric of the second security of the second security of the second	a)
MARQUES LOPEZ	2/21/08
Inspector's Name (Please Print)	Date of Inspection
	2/09
Inspector's Signature	Approximate Date of Next Inspection

**COMMENTS:** ON FEBRUARY 21, 2008 I VISITED THIS FACILITY TO CONDUCT THE ANNUAL COMPLIANCE INSPECTION. THE FACILITY NO LONGER DOES DRY CLEANING, IT IS NOW A DROP STORE.