



Department of Environmental Protection

FILE

Jeb Bush
Governor

Southeast District
P.O. Box 15425
West Palm Beach, Florida 33416

David B. Struhs
Secretary

November 26, 2002

NOTICE OF AIR POLLUTION PERMIT

ELECTRONIC CORRESPONDENCE
Phernandez@Miami-Airport.com

ISSUED TO:

Miami-Dade Aviation Department
P.O. Box 592075
Miami, FL 33159

Permit Number: 0250393-005-AF
Issue Date: November 26, 2002
Expiration Date: November 25, 2007

Authorized Representative:

Mr. Pedro Hernandez, P.E.
Manager, Environmental Engineering Division

PROJECT:

Project: FESOP permit renewal.
Facility Description: An Airport Support facility (SIC # 4581)
Location: Miami-Dade County, Florida, 33122
Lat./Long.: 25° 47' 54" N / 80° 17' 19" W
UTM: Zone 17; 570.61 Km. E; 2853.38 Km. N

Dear Mr. Hernandez:

This is Permit Number 0250393-005-AF this permit has been issued to incorporate changes requested by the applicant and authorize operation of the emission units described in this permit.

NOTICE OF RIGHTS:

Any party to this Order has the right to seek judicial review of the permit under Section 120.68 of the Florida Statutes, by filing a notice of appeal under Rule 9.110 of the Florida Rules of Appellate Procedure, with the Clerk of the Department of Environmental Protection in the Office of General Counsel at 3900 Commonwealth Boulevard, Mail Station 35, Tallahassee, Florida 32399-3000, and by filing a copy of the notice of appeal accompanied by the applicable filing fees with the appropriate District Court of Appeal. The notice must be filed within thirty days after this order is filed with the clerk of the Department.

STATEMENT OF BASIS:

This permit is issued under the provisions of Chapter 403, Florida Statutes (F.S.), and Florida Administrative Code (F.A.C.) Rules 62-4, and 62-204 through 62-297, and in conformance with all existing regulations of the Florida Department of Environmental Protection. The above named owner or operator is hereby authorized to perform the work or operate the facility shown on the application and approved drawing(s), plans, and other documents attached hereto or on file with the Department, in accordance with the terms and conditions of this permit.

"More Protection, Less Process"

Printed on recycled paper.

PART I -- SUMMARY INFORMATION

PERMIT CONTENTS:

Part I -- Summary Information
Part II -- Facility-Wide Specific Conditions
Part III -- Emission Unit Specific Conditions
Appendix A -- General Conditions
Appendix B -- 40 CFR 60 Subpart Kb
Attachment C--Summary of all Floating and Fixed Roof Tanks at the facility

OPERATE: This permit addresses the following air pollution emission units:

Emissions Unit Number	Emissions Unit Description
004	Internal Floating Roof Tanks (Includes tanks No. 13,14,15,16,17 and 18) storing Jet Kerosene
005	Vertical Fixed Roof Tanks (Includes tanks No. 3,5,7,8,9,24,25, and 26) storing Jet Kerosene
007	Twenty Seven (27) emergency diesel generators, with less than 600 HP
008	Fourteen (14) emergency diesel generators with more than 600 HP
010	Chemical Usage
018	Loading Rack

This permit also addresses the following air pollution activities which are deemed to be exempt from permitting, based on the information provided by the applicant to the Department:

Emissions Unit Number	Exempt Activity Description
013	Three Vertical Fixed Roof Tanks (Diesel and Vehicle fuel of total capacity 30,000 gal)
014	Sand Blasting operations
015	Welding operations
016	Wood Working Operations
017	Part Washers (System One units) and Fuel filters changes, spills

Exempt activities have no emission unit specific conditions, but are subject to applicable general pollutant emission limiting standards specified in Part II of this permit.

SIGNIFICANT DATES:

Public Notice of Intent Published: October 26, 2002
Additional Information Received: June 10, 2002
Application Received: February 19, 2002

PERMIT HISTORY:

Permit No. 0250393-004-AF issued June 29, 1998.
Permit No. 0250393-001-AF issued February 07, 1997.
Permit No. AO 13-199202 issued July 26 1991.
Permit No. AC 13-272642 issued November 17 1995.

This permit supersedes all permits issued previously.

PART II -- FACILITY-WIDE SPECIFIC CONDITIONS

Conditions in this part generally apply to all emission units and activities covered under this permit.

1.0 Administrative Requirements

- 1.1 **Regulating Agencies:** All applications, tests, reports, notifications, or other submittals required by this permit shall be submitted to the Florida Department of Environmental Protection, Southeast District Office, Air Program at PO Box 15425, West Palm Beach, Florida, 33416 (street address 400 North Congress Avenue, West Palm Beach, Florida, 33401, phone (561) 681-6600, Fax (561) 681-6790). In addition, copies shall be submitted to Dade County Department of Environmental Resources Management, Air Quality Management Division, 33 SW Second Avenue, Suite 900, Miami, Florida, 33130 phone (305) 372-6925).
- 1.2 **Citation Format:** In this permit, references to F.A.C. Rule 62-xxx refer to rules promulgated under Title 62 of the Florida Administrative Code; references (if any) to 40 CFR 60.xx (or 61.xx or 63.xx) refer to regulations codified under Part 60 (or 61 or 63) of Title 40 of the Code of Federal Regulations.
- 1.3 **Specific and General Conditions:** The owner or operator shall be subject to the specific conditions of this permit and the owner or operator shall be aware of, and operate under, the attached General Conditions, attached as Appendix A of this permit. General Conditions are binding and enforceable pursuant to Chapter 403, F.S.
[Rule 62-4.160, F.A.C.]
- 1.4 **Applicable Regulations:** This facility is subject to regulation of Florida Administrative Code (F.A.C.) Rules 62-4 and 62-204 through 62-297 and 40 CFR Kb. Issuance of this permit does not relieve the facility owner or operator from compliance with any other applicable federal, state or local permitting requirements or other regulations.
- 1.5 **Other Permits:** This air pollution permit does not preclude the owner or operator from obtaining any other types of required permits, licenses or certifications from this Department or other departments or agencies.
- 1.6 **Renewal of This Permit Required:** An application for renewal of this operation permit must be submitted to the Department of Environmental Protection, Southeast District Office, Air Program at least 60 days prior to the expiration date of this permit. To apply for an operation permit, the applicant shall submit the appropriate application form in quadruplicate, the appropriate application fee, all required compliance test results, and such additional information as the Department may by law require.
[Rules 62-4.030, 62-4.050, and 62-4.220, F.A.C.]

{Permit note: Public notice may be required again at the time of renewal or revision of this permit if the facility or permit is materially changed from that described by this permit.}

[Rule 62-210.350(4)(a), F.A.C.]

2.0 General Pollutant Emission Limiting Standards

- 2.1 **Objectionable Odor Prohibited:** No person shall cause, suffer, allow or permit the discharge of air pollutants which cause or contribute to an objectionable odor.
- {Permitting note: Objectionable odor is defined in Rule 62-210.200(181), F.A.C., as any odor present in the outdoor atmosphere which by itself or in combination with other odors, is or may be harmful or injurious to human health or welfare, which unreasonably interferes with the comfortable use and enjoyment of life or property, or which creates a nuisance.}*
- [Rule 62-296.320(2), F.A.C.]
- 2.2 **General Visible Emissions Standard:** Unless otherwise specified by permit or rule, no person shall cause, let, permit, suffer or allow to be discharged into the atmosphere the emissions of air pollutants from any activity, the density of which is equal to or greater than 20 percent opacity.
[Rule 62-296.320(4)(b), F.A.C.]

- 2.3 Volatile Organic Compounds/Organic Solvents Emissions: No person shall store, pump, handle, process, load, unload or use in any process or installation, volatile organic compounds or organic solvents without applying known and existing vapor emission control devices or systems deemed necessary and ordered by the Department.

Such controls include the following:

- ◆ Tightly cover or close all VOC containers when they are not in use.
- ◆ Tightly cover all open tanks that contain VOCs when they are not in use.
- ◆ Maintain all pipes, valves, fittings, etc., which handle VOCs in good operating condition.
- ◆ Confine rags used with VOCs to tightly closed, fireproof containers when not in use.
- ◆ Immediately confine and clean up VOC spills and make sure wastes are placed in closed containers for reuse, recycling or proper disposal.

[Rule 62-296.320(1), F.A.C.]

- 2.4 Unconfined Emissions of Particulate Matter: No person shall cause, let, permit, suffer or allow the emissions of unconfined particulate matter from any activity, including vehicular movement; transportation of materials; construction, alteration, demolition or wrecking; or industrially related activities such as loading, unloading, storing or handling; without taking reasonable precautions to prevent such emissions.

Reasonable precautions include the following:

- ◆ Paving and maintenance of roads, parking areas and yards.
- ◆ Removal of particulate matter from roads and other paved areas under the control of the owner or operator of the facility to prevent reentrainment, and from buildings or work areas to prevent particulate from becoming airborne.
- ◆ Landscaping or planting of vegetation.

[Rule 62-296.320(4)(c), F.A.C.]

3.0 Operation Requirements

- 3.1 Circumvention: No person shall circumvent any air pollution control device, or allow the emission of air pollutants without the applicable air pollution control device operating properly.

[Rule 62-210.650, F.A.C.]

- 3.2 Excess Emissions: Excess emissions resulting from startup, shutdown or malfunction of any emissions unit shall be permitted providing best operational practices to minimize emissions are adhered to, and the duration of excess emissions shall be minimized but in no case exceeds two hours in any 24 hour period unless specifically authorized by the Department for longer duration.

Excess emissions which are caused entirely or in part by poor maintenance, poor operation, or any other equipment or process failure which may reasonably be prevented during startup, shutdown, or malfunction shall be prohibited.

[Rule 62-210.700, F.A.C.]

4.0 Compliance Testing Requirements

- 4.1 Test Notification: Unless otherwise specified in this permit, the Department of Environmental Protection, Southeast District Office, Air Program shall be notified in writing of expected compliance test dates at least fifteen (15) days prior to compliance testing. The notification shall include the following information: the date, time, and location of each test, and the test contact person who will be responsible for coordinating and having such test conducted for the owner.

[Rule 62-297.310(7)(a), F.A.C.]

4.2 **Testing at Capacity:** Compliance testing shall be conducted with the emission units operating at the permitted capacity (90 to 100% of the maximum permitted operation rate of the emission units). If emissions unit is not tested at permitted capacity, the emission unit shall not be operated above 110% of the test load until a new test showing compliance is conducted. Operation of the emissions unit above 110% of the test load is allowed for no more than 15 days for the purpose of conducting additional compliance testing to regain the authority to operate at the permitted capacity.

[Rule 62-297.310(2), F.A.C.]

4.3 **Special Compliance Tests:** When the Department, after investigation, has good reason (such as complaints, increased visible emissions or questionable maintenance of control equipment) to believe that any applicable emission standard in Rules 62-204 through 62-297 or in a permit issued pursuant to those rules is being violated, it shall require the owner or operator of the emissions unit to conduct compliance tests which identify the nature and quantity of pollutant emissions from the emissions unit and to provide a report on the results of said tests to the Department.

[Rule 62-297.310(7)(b), F.A.C.]

5.0 Reporting and Record Keeping Requirements

5.1 **Report Excess Emissions:** In case of excess emissions resulting from malfunctions, each owner or operator shall notify the Department in accordance with Rule 62-4.130, F.A.C. (condition 5.2 below). A full written report on the malfunctions shall be submitted in a quarterly report, if requested by the Department.

[Rule 62-210.700(6), F.A.C.]

5.2 **Report Plant Operation Problems:** If the owner or operator is temporarily unable to comply with any of the conditions of the permit due to breakdown of equipment or destruction by hazard of fire, wind or by other cause, the owner or operator shall immediately notify the Department. Notification shall include pertinent information as to the cause of the problem, and what steps are being taken to correct the problem and to prevent its recurrence, and where applicable, the owner's intent toward reconstruction of destroyed facilities. Such notification does not release the owner or operator from any liability for failure to comply with Department rules.

[Rule 62-4.130, F.A.C.]

5.3 **Retain Records:** All records required by this permit shall be kept by the owner or operator and made available for Department inspection for a minimum of five (5) from the date of such records.

[Rule 62-4.070(3), F.A.C.]

5.4 **Compliance Test Reports:** Compliance test reports shall be submitted to the Department of Environmental Protection, Southeast District Office, Air Compliance Section, as soon as practical, but no later than 45 days after the last sampling run of each test is completed.

Test reports shall provide sufficient detail on the emissions unit tested and the test procedures used to allow the Department to determine if the test was properly conducted and the test results properly computed. Test reports, other than for an EPA or DEP Method 9 test, shall include the following information and other information as necessary to make a complete report required pursuant to Rule 297.310(8)(c), F.A.C.:

- ◆ The normal type and amount of fuels used and materials processed, and the types and amounts of fuels used and material processed during each test run.
- ◆ The means, raw data and computations used to determine the amount of fuels used and materials processed, if necessary to determine compliance with an applicable emission limiting standard.
- ◆ The type of air pollution control devices installed on the emissions unit, their general condition, their normal operating parameters (pressure drops, total operating current and GPM scrubber water), and their operating parameters during each test run.
- ◆ All measured and calculated data required to be determined by each applicable test procedure for each run.
- ◆ The detailed calculations for one run that relate the collected data to the calculated emission rate.
- ◆ The applicable emission standard and the resulting maximum allowable emission rate for the emissions unit, plus the test result in the same form and unit of measure.

[Rules 62-297.310(8)(a) & (b), F.A.C.]

- 5.5 **Annual Report Required:** On or before March 1 of each calendar year, a completed DEP Form 62-210.900(5), Annual Operating Report (AOR) Form for Air Pollutant Emitting Facility, shall be submitted to the Department of Environmental Protection, Southeast District Office, Air Program. **Included with this report shall be additional reports, if any, required by this permit in Part III -- Emission Unit Specific Conditions.**
[Rule 62-210.370(3), F.A.C.]

PART III A -- EMISSION UNIT SPECIFIC CONDITIONS

This part of this permit addresses the following emission units:

Emissions Unit Number	Emissions Unit Description
007	Twenty Seven (27) emergency diesel generators, with less than 600 HP
008	Fourteen (14) emergency diesel generators with more than 600 HP

Essential Potential to Emit (PTE) Parameters

- 1.1 **Permitted Capacity.** The power output from all **Diesel Generators** shall not exceed **1,934,200 KW-hr** in any given consecutive 12-month period.

[Rule 62-210.200(PTE), F.A.C. and Permit 0250393-004-AF]

[Permitting Note: This condition will limit NOx emissions from these units to 40 tons per year. This restriction is based on the AP-42 Emission Factor of 18.8 gm/Kw-hr and if the Emission Factor is revised by the EPA then the Kw-hr restriction shall be modified accordingly.]

Record Keeping and Reporting Requirements

- 1.2 The Permittee shall record and maintain records for each Diesel Generator of the hours of operation, including operation for repairs or maintenance on a monthly basis.

[Permit 0250393-004-AF]

Compliance with Kw-hr limit shall be determined based on rating and the hours of operation of each generator. From the monthly records of hours of operation, and Kw-hr rating of each emergency generator, the Permittee shall record and maintain a rolling 12-month cumulative hours of operation, and 12-month rolling total calculated Kw-hr for all generators. This record keeping shall be done no later than 14th of the following month.

{Permitting note: The rolling 12-month rolling records shall be used to demonstrate compliance with the limitation in specific condition 1.1.}

[Rule 62-4.070, F.A.C. and Permit 0250393-004-AF]

- 1.3 **Reports:** Attached to the annual operation report shall be the following records that were recorded in the previous calendar year. This report shall be submitted to the Department on or before March 1 of each calendar year.

- ◆ The highest 12-month consecutive total Kw-hrs calculated, and the total hours of operation.

All records required under this section shall be maintained by the Permittee for a period of five years following the date of such record.

[Rules 62-210.370(3), and 62-4.070, F.A.C., Permit 0250393-004-AF]

PART III B -- EMISSION UNIT SPECIFIC CONDITIONS

This part of this permit addresses the following emission units:

Emissions Unit Number	Emissions Unit Description
004	Internal Floating Roof Tanks (Tanks No. 13, 14, 15, 16, 17 and 18)
005	Vertical Fixed Roof Tanks. (Tanks No. 3, 5, 7, 8, 9, 24, 25 and 26)
010	Chemical Usage
018	Loading Rack

{Tanks No. 24, 25 and 26 were installed after July 23, 1984; therefore they are subject to 40 CFR Subpart Kb. None of the fixed and floating roof tanks with Jet Kerosene are subject to VOC control requirements contained in the NSPS Subpart K, Ka or Kb as the vapor pressure of the Jet Kerosene is approximately 0.75 mm Hg at ambient temperature which is significantly below regulatory limits.)

The following specific conditions apply to the emissions units listed above:

Essential Potential to Emit (PTE) Parameters

- 1.1 These emission units are allowed to operate continuously.
[Rule 62-210.200(PTE), F.A.C.]

Emission Limitations and Standards

Tanks 24, 25, & 26

- 1.2 Tanks 24, 25, 26 shall comply with the requirements in 40CFR Subpart Kb (Appendix--B). The owner or operator of each storage vessel with a design capacity greater than or equal to 151 m³ storing a liquid with a maximum true vapor pressure that is normally less than 5.2 kPa shall notify the Department within 30 days when the maximum true vapor pressure of the liquid exceeds the respective maximum true vapor pressure values for each volume range.
[40 CFR 60.116b(d)]

Available data on the storage temperature may be used to determine the maximum true vapor pressure as determined below.

- (1) For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.
- (2) For crude oil or refined petroleum products the vapor pressure may be obtained by the following:
 - (i) Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference—see 40 CFR 60.17), unless the Administrator specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).
 - (ii) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.

[40 CFR 60.116b(e)]

Record Keeping and Reporting Requirements

- 1.3 Reports: These emission units shall report total fuel throughput and material (chemicals) usage in the annual operating report. This report shall be submitted to the Department on or before March 1 of each calendar year.
[Rule 62-4.070, F.A.C. and Permit 0250393-004-AF]

Executed in West Palm Beach, Florida.

STATE OF FLORIDA DEPARTMENT
OF ENVIRONMENTAL PROTECTION


 11-26-02
Thomas Tittle Date
District Air Program Administrator
Southeast District

TT/LT/md

cc:

Patrick Wong, DERM (e-mail: WONGP@miamidade.gov)

FILING AND ACKNOWLEDGMENT: FILED, on this date, pursuant to § 120.52(7), F.S., with the designated Department Clerk, receipt of which is hereby acknowledged.

 11/26/02
Clerk Date

APPENDIX - A

GENERAL CONDITIONS Pursuant Rule 62-4.160, Florida Administrative Code (F.A.C.):

1. The terms, conditions, requirements, limitations and restrictions set forth in this permit, are "permit conditions" and are binding and enforceable pursuant to Sections 403.141, 403.727, or 403.859 through 403.861, Florida Statutes (F.S.) The permittee is placed on notice that the Department will review this permit periodically and may initiate enforcement action for any violation of these conditions.
 2. This permit is valid only for the specific processes and operations applied for and indicated in the approved drawings or exhibits. Any unauthorized deviation from the approved drawings, exhibits, specifications, or conditions of this permit may constitute grounds for revocation and enforcement action by the Department.
 3. As provided in subsections 403.987(6) and 403.722(5), F.S., the issuance of this permit does not convey any vested rights or any exclusive privileges. Neither does it authorize any injury to public or private property or any invasion of personal rights, nor any infringement of federal, state, or local laws or regulations. This permit is not a waiver of or approval of any other department permit that may be required for other aspects of the total project which are not addressed in this permit.
 4. This permit conveys no title to land or water, does not constitute State recognition or acknowledgment of title, and not constitute authority for the use of submerged lands unless herein provided and the necessary title or leasehold interests have been obtained from the State. Only the Trustees of the Internal Improvement Trust Fund may express State opinion as to title.
 5. This permit does not relieve the permittee from liability for harm or injury to human health or welfare, animal, or plant life, or property caused by the construction or operation of this permitted source, or from penalties therefore; nor does it allow the permittee to cause pollution in contravention of Florida Statutes and Department rules, unless specifically authorized by an order from the Department.
 6. The permittee shall properly operate and maintain the facility and systems of treatment and control (and related appurtenances) that are installed and used by the permittee to achieve compliance with the conditions of this permit, as required by Department rules. This provision includes the operation of backup or auxiliary facilities or similar systems when necessary to achieve compliance with the conditions of the permit and when required by Department rules.
 7. The permittee, by accepting this permit, specifically agrees to allow authorized Department personnel, upon presentation of credentials or other documents as may be required by law and at reasonable times, access to the premises where the permitted activity is located or conducted to:
 - a. Have access to and copy any records that must be kept under conditions of the permit;
 - b. Inspect the facility, equipment, practices, or operations regulated or required under this permit; and
 - c. Sample or monitor any substances or parameters at any location reasonably necessary to assure compliance with this permit or Department rules. Reasonable time may depend on the nature of the concern being investigated.
 8. If, for any reason, the permittee does not comply with or will be unable to comply with any condition or limitation specified in this permit, the permittee shall immediately provide the Department with the following information:
 - a. A description of and cause of noncompliance; and
 - b. The period of noncompliance, including dates and times; or, if not corrected, the anticipated time the noncompliance is expected to continue, and steps being taken to reduce, eliminate, and prevent recurrence of the noncompliance. The permittee shall be responsible for any and all damages which may result and may be subject to enforcement action by the Department for penalties or for revocation of this permit.
 9. In accepting this permit, the permittee understands and agrees that all records, notes, monitoring data and other information relating to the construction or operation of this permitted source which are submitted to the Department
-

APPENDIX - A

GENERAL CONDITIONS CONTINUED:

may be used by the Department as evidence in any enforcement case involving the permitted source arising under the Florida Statutes or Department rules, except where such use is prescribed by Sections 403.111 and 403.73, F.S. Such evidence shall only be used to the extent it is consistent with the Florida Rules of Civil Procedure and appropriate evidentiary rules.

10. The permittee agrees to comply with changes in Department rules and Florida Statutes after a reasonable time for compliance; provided, however, the permittee does not waive any other rights granted by Florida Statutes or Department rules. A reasonable time for compliance with a new or amended surface water quality standard, other than those standards addressed in Rule 62-302.500, F.A.C., shall include a reasonable time to obtain or be denied a mixing zone for the new or amended standard.
11. This permit is transferable only upon Department approval in accordance with Rules 62-4. 120 and 62-730. 300, F.A.C., as applicable. The permittee shall be liable for any non-compliance of the permitted activity until the transfer is approved by the Department.
12. This permit or a copy thereof shall be kept at the work site of the permitted activity.
13. The permittee shall comply with the following:
 - a. Upon request, the permittee shall furnish all records and plans required under Department rules. During enforcement actions, the retention period for all records will be extended automatically unless otherwise stipulated by the Department.
 - b. The permittee shall hold at the facility or other location designated by this permit records of all monitoring information (including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation) required by the permit, copies of all reports required by this permit, and records of all data used to complete the application for this permit. These materials shall be retained at least three years from the date of the sample, measurement, report, or application unless otherwise specified by Department rule.
 - c. Records of monitoring information shall include:
 - (1) The date, exact place, and time of sampling or measurements;
 - (2) The person responsible for performing the sampling or measurements;
 - (3) The dates analyses were performed;
 - (4) The person responsible for performing the analyses;
 - (5) The analytical techniques or methods used;
 - (6) The results of such analyses.
14. When requested by the Department, the permittee shall within a reasonable time furnish any information required by law which is needed to determine compliance with the permit. If the permittee becomes aware the relevant facts were not submitted or were incorrect in the permit application or in any report to the Department, such facts or information shall be corrected promptly.

Specific Authority 403. 061, 403. 087, 403. 088 FS. Law Implemented 403. 061, 403. 087, 403. 088 FS. History – New 8-31-88, Amended 10-4-89, 7-11-93, Formerly 17-4. 160.

APPENDIX -B

[Last Updated 2/7/02]

{Source: Federal Register dated 7/1/98, revised 2/7/02 to reflect FR 10/17/00 and FR 12/14/00}

Subpart Kb — Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984

§ 60.110b Applicability and designation of affected facility.

(a) Except as provided in paragraphs (b), (c), and (d) of this section, the affected facility to which this subpart applies is each storage vessel with a capacity greater than or equal to 40 cubic meters (m³) that is used to store volatile organic liquids (VOL's) for which construction, reconstruction, or modification is commenced after July 23, 1984.

(b) Except as specified in paragraphs (a) and (b) of § 60.116b, storage vessels with design capacity less than 75 m³ are exempt from the General Provisions (part 60, subpart A) and from the provisions of this subpart.

(c) Except as specified in paragraphs (a) and (b) of § 60.116b, vessels either with a capacity greater than or equal to 151 m³ storing a liquid with a maximum true vapor pressure less than 3.5 kPa or with a capacity greater than or equal to 75 m³ but less than 151 m³ storing a liquid with a maximum true vapor pressure less than 15.0 kPa are exempt from the General Provisions (part 60, subpart A) and from the provisions of this subpart.

(d) This subpart does not apply to the following:

- (1) Vessels at coke oven by-product plants.
- (2) Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
- (3) Vessels permanently attached to mobile vehicles such as trucks, rail-cars, barges, or ships.
- (4) Vessels with a design capacity less than or equal to 1,589.874 m³ used for petroleum or condensate stored, processed, or treated prior to custody transfer.
- (5) Vessels located at bulk gasoline plants.
- (6) Storage vessels located at gasoline service stations.
- (7) Vessels used to store beverage alcohol.

(e) *Alternative means of compliance -- (1) Option to comply with part 65.* Owners or operators may choose to comply with 40 CFR part 65, subpart C, to satisfy the requirements of §§ 60.112b through 60.117b for storage vessels that are subject to this subpart that meet the specifications in paragraphs (e)(1)(i) and (ii) of this section. When choosing to comply with 40 CFR part 65, subpart C, the monitoring requirements of § 60.116b(c), (e), (f)(1), and (g) still apply. Other provisions applying to owners or operators who choose to comply with 40 CFR part 65 are provided in 40 CFR 65.1.

(i) A storage vessel with a design capacity greater than or equal to 151 m³ containing a VOL that, as stored, has a maximum true vapor pressure equal to or greater than 5.2 kPa; or

(ii) A storage vessel with a design capacity greater than 75 m³ but less than 151 m³ containing a VOL that, as stored, has a maximum true vapor pressure equal to or greater than 27.6 kPa.

(2) *Part 60, subpart A.* Owners or operators who choose to comply with 40 CFR part 65, subpart C, must also comply with §§ 60.1, 60.2, 60.5, 60.6, 60.7(a)(1) and (4), 60.14, 60.15, and 60.16 for those storage vessels. All sections and paragraphs of subpart A of this part that are not mentioned in this paragraph (e)(2) do not apply to owners or operators of storage vessels complying with 40 CFR part 65, subpart C, except that provisions required to be met prior to implementing 40 CFR part 65 still apply. Owners and operators who choose to comply with 40 CFR part 65, subpart C, must comply with 40 CFR part 65, subpart A.

(3) *Internal floating roof report.* If an owner or operator installs an internal floating roof and, at initial startup, chooses to comply with 40 CFR part 65, subpart C, a report shall be furnished to the Administrator stating that the control equipment meets the specifications of 40 CFR 65.43. This report shall be an attachment to the notification required by 40 CFR 65.5(b).

(4) *External floating roof report.* If an owner or operator installs an external floating roof and, at initial startup, chooses to comply with 40 CFR part 65, subpart C, a report shall be furnished to the Administrator stating that the control equipment meets the specifications of 40 CFR 65.44. This report shall be an attachment to the notification required by 40 CFR 65.5(b).

APPENDIX -B

§ 60.111b Definitions.

Terms used in this subpart are defined in the Act, in subpart A of this part, or in this subpart as follows:

- (a) *Bulk gasoline plant* means any gasoline distribution facility that has a gasoline throughput less than or equal to 75,700 liters per day. Gasoline throughput shall be the maximum calculated design throughput as may be limited by compliance with an enforceable condition under Federal requirement or Federal, State or local law, and discoverable by the Administrator and any other person.
- (b) *Condensate* means hydrocarbon liquid separated from natural gas that condenses due to changes in the temperature or pressure, or both, and remains liquid at standard conditions.
- (c) *Custody transfer* means the transfer of produced petroleum and/or condensate, after processing and/or treatment in the producing operations, from storage vessels or automatic transfer facilities to pipelines or any other forms of transportation.
- (d) *Fill* means the introduction of VOL into a storage vessel but not necessarily to complete capacity.
- (e) *Gasoline service station* means any site where gasoline is dispensed to motor vehicle fuel tanks from stationary storage tanks.
- (f) *Maximum true vapor pressure* means the equilibrium partial pressure exerted by the stored VOL at the temperature equal to the highest calendar-month average of the VOL storage temperature for VOL's stored above or below the ambient temperature or at the local maximum monthly average temperature as reported by the National Weather Service for VOL's stored at the ambient temperature, as determined:
- (1) In accordance with methods de-scribed in American Petroleum institute Bulletin 2517, Evaporation Loss From External Floating Roof Tanks, (incorporated by reference—see § 60.17); or
 - (2) As obtained from standard reference texts; or
 - (3) As determined by ASTM Method D2879–83, 96, or 97 (incorporated by reference— see § 60.17);
 - (4) Any other method approved by the Administrator.
- (g) *Reid vapor pressure* means the absolute vapor pressure of volatile crude oil and volatile nonviscous petroleum liquids except liquified petroleum gases, as determined by ASTM D323–82 or 94 (incorporated by reference—see § 60.17).
- (h) *Petroleum* means the crude oil removed from the earth and the oils derived from tar sands, shale, and coal.
- (i) *Petroleum liquids* means petroleum, condensate, and any finished or intermediate products manufactured in a petroleum refinery.
- (j) *Storage vessel* means each tank, reservoir, or container used for the storage of volatile organic liquids but does not include:
- (1) Frames, housing, auxiliary supports, or other components that are not directly involved in the containment of liquids or vapors; or
 - (2) Subsurface caverns or porous rock reservoirs.
- (k) *Volatile organic liquid (VOL)* means any organic liquid which can emit volatile organic compounds into the atmosphere except those VOL's that emit only those compounds which the Administrator has determined do not contribute appreciably to the formation of ozone. These compounds are identified in EPA statements on ozone abatement policy for SIP revisions (42 FR 35314, 44 FR 32042, 45 FR 32424, and 45 FR 48941).
- (l) *Waste* means any liquid resulting from industrial, commercial, mining or agricultural operations, or from community activities that is discarded or is being accumulated, stored, or physically, chemically, or biologically treated prior to being discarded or recycled.

[52 FR 11429, Apr. 8, 1987, as amended at 54 FR 32973, Aug. 11, 1989]

APPENDIX -B

§ 60.112b Standard for volatile organic compounds (VOC).

(a) The owner or operator of each storage vessel either with a design capacity greater than or equal to 151 m³ containing a VOL that, as stored, has a maximum true vapor pressure equal to or greater than 5.2 kPa but less than 76.6 kPa or with a design capacity greater than or equal to 75 m³ but less than 151 m³ containing a VOL that, as stored, has a maximum true vapor pressure equal to or greater than 27.6 kPa but less than 76.6 kPa, shall equip each storage vessel with one of the following:

(1) A fixed roof in combination with an internal floating roof meeting the following specifications:

(i) The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.

(ii) Each internal floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof:

(A) A foam- or liquid-filled seal mounted in contact with the liquid (liquid-mounted seal). A liquid-mounted seal means a foam- or liquid-filled seal mounted in contact with the liquid between the wall of the storage vessel and the floating roof continuously around the circumference of the tank.

(B) Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.

(C) A mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.

(iii) Each opening in a noncontact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.

(iv) Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.

(v) Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.

(vi) Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting.

(vii) Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.

(viii) Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.

(ix) Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.

(2) An external floating roof. An external floating roof means a pontoon-type or double-deck type cover that rests on the liquid surface in a vessel with no fixed roof. Each external floating roof must meet the following specifications:

(i) Each external floating roof shall be equipped with a closure device between the wall of the storage vessel and the roof edge. The closure device is to consist of two seals, one above the other. The lower seal is referred to as the primary seal, and the upper seal is referred to as the secondary seal.

(A) The primary seal shall be either a mechanical shoe seal or a liquid-mounted seal. Except as provided in § 60.113b(b)(4), the seal shall completely cover the annular space between the edge of the floating roof and tank wall.

(B) The secondary seal shall completely cover the annular space between the external floating roof and the wall of the storage vessel in a continuous fashion except as allowed in § 60.113b(b)(4).

(ii) Except for automatic bleeder vents and rim space vents, each opening in a noncontact external floating roof shall provide a projection below the liquid surface. Except for automatic bleeder vents, rim space vents, roof drains, and leg sleeves, each opening in the roof is to be equipped with a gasketed cover, seal, or lid that is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. Automatic

APPENDIX -B

bleeder vents are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. Rim vents are to be set to open when the roof is being floated off the roof legs supports or at the manufacturer's recommended setting. Automatic bleeder vents and rim space vents are to be gasketed. Each emergency roof drain is to be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening.

(iii) The roof shall be floating on the liquid at all times (i.e., off the roof leg supports) except during initial fill until the roof is lifted off leg supports and when the tank is completely emptied and subsequently refilled. The process of filling, emptying, or refilling when the roof is resting on the leg supports shall be continuous and shall be accomplished as rapidly as possible.

(3) A closed vent system and control device meeting the following specifications:

(i) The closed vent system shall be designed to collect all VOC vapors and gases discharged from the storage vessel and operated with no detectable emissions as indicated by an instrument reading of less than 500 ppm above background and visual inspections, as determined in part 60, subpart VV, § 60.485(b).

(ii) The control device shall be designed and operated to reduce inlet VOC emissions by 95 percent or greater. If a flare is used as the control device, it shall meet the specifications described in the general control device requirements (§ 60.18) of the General Provisions.

(4) A system equivalent to those described in paragraphs (a)(1), (a)(2), or (a)(3) of this section as provided in § 60.114b of this subpart.

(b) The owner or operator of each storage vessel with a design capacity greater than or equal to 75 m³ which contains a VOL that, as stored, has a maximum true vapor pressure greater than or equal to 76.6 kPa shall equip each storage vessel with one of the following:

(1) A closed vent system and control device as specified in § 60.112b(a)(3).

(2) A system equivalent to that described in paragraph (b)(1) as provided in § 60.114b of this subpart.

(c) *Site-specific standard for Merck & Co., Inc.'s Stonewall Plant in Elkton, Virginia.* This paragraph applies only to the pharmaceutical manufacturing facility, commonly referred to as the Stonewall Plant, located at Route 340 South, in Elkton, Virginia ("site").

(1) For any storage vessel that otherwise would be subject to the control technology requirements of paragraphs (a) or (b) of this section, the site shall have the option of either complying directly with the requirements of this subpart, or reducing the site-wide total criteria pollutant emissions cap (total emissions cap) in accordance with the procedures set forth in a permit issued pursuant to 40 CFR 52.2454. If the site chooses the option of reducing the total emissions cap in accordance with the procedures set forth in such permit, the requirements of such permit shall apply in lieu of the otherwise applicable requirements of this subpart for such storage vessel.

(2) For any storage vessel at the site not subject to the requirements of 40 CFR 60.112b (a) or (b), the requirements of 40 CFR 60.116b (b) and (c) and the General Provisions (subpart A of this part) shall not apply. [52 FR 11429, Apr. 8, 1987, as amended at 62 FR 52641, Oct. 8, 1997]

§ 60.113b Testing and procedures.

The owner or operator of each storage vessel as specified in § 60.112b(a) shall meet the requirements of paragraph (a), (b), or (c) of this section. The applicable paragraph for a particular storage vessel depends on the control equipment installed to meet the requirements of § 60.112b.

(a) After installing the control equipment required to meet § 60.112b(a)(1) (permanently affixed roof and internal floating roof), each owner or operator shall:

(1) Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to filling the storage vessel with VOL. If there are holes, tears, or other openings in the primary seal, the secondary seal, or the seal fabric or defects in the internal floating roof, or both, the owner or operator shall repair the items before filling the storage vessel.

(2) For Vessels equipped with a liquid-mounted or mechanical shoe primary seal, visually inspect the internal floating roof and the primary seal or the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or

APPENDIX -B

tears in the seal fabric, the owner or operator shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Administrator in the inspection report required in § 60.115b(a)(3). Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.

(3) For vessels equipped with a double-seal system as specified in § 60.112b(a)(1)(ii)(B):

(i) Visually inspect the vessel as specified in paragraph (a)(4) of this section at least every 5 years; or

(ii) Visually inspect the vessel as specified in paragraph (a)(2) of this section.

(4) Visually inspect the internal floating roof, the primary seal, the secondary seal (if one is in service), gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the owner or operator shall repair the items as necessary so that none of the

conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in paragraphs (a)(2) and (a)(3)(ii) of this section and at intervals no greater than 5 years in the case of vessels specified in paragraph (a)(3)(i) of this section.

(5) Notify the Administrator in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by paragraphs (a)(1) and (a)(4) of this section to afford the Administrator the opportunity to have an observer present. If the inspection required by paragraph (a)(4) of this section is not planned and the owner or operator could not have known about the inspection 30 days in advance or refilling the tank, the owner or operator shall notify the Administrator at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Administrator at least 7 days prior to the refilling.

(b) After installing the control equipment required to meet § 60.112b(a)(2) (external floating roof), the owner or operator shall:

(1) Determine the gap areas and maximum gap widths, between the primary seal and the wall of the storage vessel and between the secondary seal and the wall of the storage vessel according to the following frequency.

(i) Measurements of gaps between the tank wall and the primary seal (seal gaps) shall be performed during the hydrostatic testing of the vessel or within 60 days of the initial fill with VOL and at least once every 5 years thereafter.

(ii) Measurements of gaps between the tank wall and the secondary seal shall be performed within 60 days of the initial fill with VOL and at least once per year thereafter.

(iii) If any source ceases to store VOL for a period of 1 year or more, subsequent introduction of VOL into the vessel shall be considered an initial fill for the purposes of paragraphs (b)(1)(i) and (b)(1)(ii) of this section.

(2) Determine gap widths and areas in the primary and secondary seals individually by the following procedures:

(i) Measure seal gaps, if any, at one or more floating roof levels when the roof is floating off the roof leg supports.

(ii) Measure seal gaps around the entire circumference of the tank in each place where a 0.32-cm diameter uniform probe passes freely (without forcing or binding against seal) between the seal and the wall of the storage vessel and measure the circumferential distance of each such location.

(iii) The total surface area of each gap described in paragraph (b)(2)(ii) of this section shall be determined by using probes of various widths to measure accurately the actual distance from the tank wall to the seal and multiplying each such width by its respective circumferential distance.

(3) Add the gap surface area of each gap location for the primary seal and the secondary seal individually and divide the sum for each seal by the nominal diameter of the tank and compare each ratio to the respective standards in paragraph (b)(4) of this section.

(4) Make necessary repairs or empty the storage vessel within 45 days of identification in any inspection for seals not meeting the requirements listed in (b)(4) (i) and (ii) of this section:

(i) The accumulated area of gaps between the tank wall and the mechanical shoe or liquid-mounted primary seal shall not exceed 212 Cm² per meter of tank diameter, and the width of any

APPENDIX -B

portion of any gap shall not exceed 3.81 cm.

(A) One end of the mechanical shoe is to extend into the stored liquid, and the other end is to extend a minimum vertical distance of 61 cm above the stored liquid surface.

(B) There are to be no holes, tears, or other openings in the shoe, seal fabric, or seal envelope.

(ii) The secondary seal is to meet the following requirements:

(A) The secondary seal is to be installed above the primary seal so that it completely covers the space between the roof edge and the tank wall except as provided in paragraph (b)(2)(iii) of this section.

(B) The accumulated area of gaps between the tank wall and the secondary seal shall not exceed 21.2 cm² per meter of tank diameter, and the width of any portion of any gap shall not exceed 1.27 cm.

(C) There are to be no holes, tears, or other openings in the seal or seal fabric.

(iii) If a failure that is detected during inspections required in paragraph (b)(1) of § 60.113b(b) cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Administrator in the inspection report required in § 60.115b(b)(4). Such extension request must include a demonstration of unavailability of alternate storage capacity and a specification of a schedule that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.

(5) Notify the Administrator 30 days in advance of any gap measurements required by paragraph (b)(1) of this section to afford the Administrator the opportunity to have an observer present.

(6) Visually inspect the external floating roof, the primary seal, secondary seal, and fittings each time the vessel is emptied and degassed.

(i) If the external floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, the owner or operator shall repair the items as necessary so that none of the conditions specified in this paragraph exist before filling or refilling the storage vessel with VOL.

(ii) For all the inspections required by paragraph (b)(6) of this section, the owner or operator shall notify the Administrator in writing at least 30 days prior to the filling or refilling of each storage vessel to afford the Administrator the opportunity to inspect the storage vessel prior to refilling. If the inspection required by paragraph (b)(6) of this section is not planned and the owner or operator could not have known about the inspection 30 days in advance of refilling the tank, the owner or operator shall notify the Administrator at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Administrator at least 7 days prior to the refilling.

(c) The owner or operator of each source that is equipped with a closed vent system and control device as required in § 60.112b (a)(3) or (b)(2) (other than a flare) is exempt from § 60.8 of the General Provisions and shall meet the following requirements.

(1) Submit for approval by the Administrator as an attachment to the notification required by § 60.7(a)(1) or, if the facility is exempt from § 60.7(a)(1), as an attachment to the notification required by § 60.7(a)(2), an operating plan containing the information listed below.

(i) Documentation demonstrating that the control device will achieve the required control efficiency during maximum loading conditions. This documentation is to include a description of the gas stream which enters the control device, including flow and VOC content under varying liquid level conditions (dynamic and static) and manufacturer's design specifications for the control device. If the control device or the closed vent capture system receives vapors, gases, or liquids other than fuels from sources that are not designated sources under this subpart, the efficiency demonstration is to include consideration of all vapors, gases, and liquids received by the closed vent capture system and control device. If an enclosed combustion device with a minimum residence time of 0.75 seconds and a minimum temperature of 816 °C is used to meet the 95 percent requirement, documentation that those conditions will exist is sufficient to meet the requirements of this paragraph.

(ii) A description of the parameter or parameters to be monitored to ensure that the control device will be operated in conformance with its design and an explanation of the criteria used for selection of that parameter (or parameters).

(2) Operate the closed vent system and control device and monitor the parameters of the closed vent system and control device in accordance with the operating plan submitted to the Administrator in accordance with paragraph (c)(1)

APPENDIX -B

of this section, unless the plan was modified by the Administrator during the review process. In this case, the modified plan applies.

(d) The owner or operator of each source that is equipped with a closed vent system and a flare to meet the requirements in § 60.112b (a)(3) or (b)(2) shall meet the requirements as specified in the general control device requirements, § 60.18 (e) and (f).

[52 FR 11429, Apr. 8, 1987, as amended at 54 FR 32973, Aug. 11, 1989]

§ 60.114b Alternative means of emission limitation.

(a) If, in the Administrator's judgment, an alternative means of emission limitation will achieve a reduction in emissions at least equivalent to the reduction in emissions achieved by any requirement in § 60.112b, the Administrator will publish in the FEDERAL REGISTER a notice permitting the use of the alternative means for purposes of compliance with that requirement.

(b) Any notice under paragraph (a) of this section will be published only after notice and an opportunity for a hearing.

(c) Any person seeking permission under this section shall submit to the Administrator a written application including:

(1) An actual emissions test that uses a full-sized or scale-model storage vessel that accurately collects and measures all VOC emissions from a given control device and that accurately simulates wind and accounts for other emission variables such as temperature and barometric pressure.

(2) An engineering evaluation that the Administrator determines is an accurate method of determining equivalence.

(d) The Administrator may condition the permission on requirements that may be necessary to ensure operation and maintenance to achieve the same emissions reduction as specified in § 60.112b.

§ 60.115b Reporting and recordkeeping requirements.

The owner or operator of each storage vessel as specified in § 60.112b(a) shall keep records and furnish reports as required by paragraphs (a), (b), or (c) of this section depending upon the control equipment installed to meet the requirements of § 60.112b. The owner or operator shall keep copies of all reports and records required by this section, except for the record required by (c)(1), for at least 2 years. The record required by (c)(1) will be kept for the life of the control equipment.

(a) After installing control equipment in accordance with § 60.112b(a)(1) (fixed roof and internal floating roof), the owner or operator shall meet the following requirements.

(1) Furnish the Administrator with a report that describes the control equipment and certifies that the control equipment meets the specifications of § 60.112b(a)(1) and § 60.113b(a)(1). This report shall be an attachment to the notification required by § 60.7(a)(3).

(2) Keep a record of each inspection performed as required by § 60.113b (a)(1), (a)(2), (a)(3), and (a)(4). Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).

(3) If any of the conditions described in § 60.113b(a)(2) are detected during the annual visual inspection required by § 60.113b(a)(2), a report shall be furnished to the Administrator within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.

(4) After each inspection required by § 60.113b(a)(3) that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in § 60.113b(a)(3)(ii), a report shall be furnished to the Administrator within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of § 60.112b(a)(1) or § 60.113b(a)(3) and list each repair made.

(b) After installing control equipment in accordance with § 60.112b(a)(2) (external floating roof), the owner or operator shall meet the following requirements.

APPENDIX -B

(1) Furnish the Administrator with a report that describes the control equipment and certifies that the control equipment meets the specifications of § 60.112b(a)(2) and § 60.113b(b)(2), (b)(3), and (b)(4). This report shall be an attachment to the notification required by § 60.7(a)(3).

(2) Within 60 days of performing the seal gap measurements required by § 60.113b(b)(1), furnish the Administrator with a report that contains:

- (i) The date of measurement.
- (ii) The raw data obtained in the measurement.
- (iii) The calculations described in § 60.113b (b)(2) and (b)(3).

(3) Keep a record of each gap measurement performed as required by § 60.113b(b). Each record shall identify the storage vessel in which the measurement was performed and shall contain:

- (i) The date of measurement.
- (ii) The raw data obtained in the measurement.
- (iii) The calculations described in § 60.113b (b)(2) and (b)(3).

(4) After each seal gap measurement that detects gaps exceeding the limitations specified by § 60.113b(b)(4), submit a report to the Administrator within 30 days of the inspection. The report will identify the vessel and contain the information specified in paragraph (b)(2) of this section and the date the vessel was emptied or the repairs made and date of repair.

(c) After installing control equipment in accordance with § 60.112b (a)(3) or (b)(1) (closed vent system and control device other than a flare), the owner or operator shall keep the following records.

- (1) A copy of the operating plan.
- (2) A record of the measured values of the parameters monitored in accordance with § 60.113b(c)(2).

(d) After installing a closed vent system and flare to comply with § 60.112b, the owner or operator shall meet the following requirements.

(1) A report containing the measurements required by § 60.18(f) (1), (2), (3), (4), (5), and (6) shall be furnished to the Administrator as required by § 60.8 of the General Provisions. This report shall be submitted within 6 months of the initial start-up date.

(2) Records shall be kept of all periods of operation during which the flare pilot flame is absent.

(3) Semiannual reports of all periods recorded under § 60.115b(d)(2) in which the pilot flame was absent shall be furnished to the Administrator.

§ 60.116b Monitoring of operations.

(a) The owner or operator shall keep copies of all records required by this section, except for the record required by paragraph (b) of this section, for at least 2 years. The record required by paragraph (b) of this section will be kept for the life of the source.

(b) The owner or operator of each storage vessel as specified in § 60.110b(a) shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. Each storage vessel with a design capacity less than 75 m³ is subject to no provision of this subpart other than those required by this paragraph.

(c) Except as provided in paragraphs (f) and (g) of this section, the owner or operator of each storage vessel either with a design capacity greater than or equal to 151 m³ storing a liquid with a maximum true vapor pressure greater than or equal to 3.5 kPa or with a design capacity greater than or equal to 75 m³ but less than 151 m³ storing a liquid with a maximum true vapor pressure greater than or equal to 15.0 kPa shall maintain a record of the VOL stored, the period of storage, and the maximum true vapor pressure of that VOL during the respective storage period.

(d) Except as provided in paragraph (g) of this section, the owner or operator of each storage vessel either with a design capacity greater than or equal to 151 m³ storing a liquid with a maximum true vapor pressure that is normally less than 5.2 kPa or with a design capacity greater than or equal to 75 m³ but less than 151 m³ storing a liquid with a maximum true vapor pressure that is normally less than 27.6 kPa shall notify the Administrator within 30 days when the maximum true vapor pressure of the liquid exceeds the respective maximum true vapor pressure values for each volume range.

APPENDIX -B

(e) Available data on the storage temperature may be used to determine the maximum true vapor pressure as determined below.

(1) For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.

(2) For crude oil or refined petroleum products the vapor pressure may be obtained by the following:

(i) Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference—see § 60.17), unless the Administrator specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).

(ii) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.

(3) For other liquids, the vapor pressure:

(i) May be obtained from standard reference texts, or

(ii) Determined by ASTM Method D2879–83, 96, or 97 (incorporated by reference—see § 60.17); or

(iii) Measured by an appropriate method approved by the Administrator; or

(iv) Calculated by an appropriate method approved by the Administrator.

(f) The owner or operator of each vessel storing a waste mixture of indeterminate or variable composition shall be subject to the following requirements.

(1) Prior to the initial filling of the vessel, the highest maximum true vapor pressure for the range of anticipated liquid compositions to be stored will be determined using the methods described in paragraph (e) of this section.

(2) For vessels in which the vapor pressure of the anticipated liquid composition is above the cutoff for monitoring but below the cutoff for controls as defined in §60.112b(a), an initial physical test of the vapor pressure is required; and a physical test at least once every 6 months thereafter is required as determined by the following methods:

(i) ASTM Method D2879–83, 96, or 97 (incorporated by reference—see § 60.17); or

(ii) ASTM Method D323–82 or 94 (incorporated by reference—see §60.17); or

(iii) As measured by an appropriate method as approved by the Administrator.

(g) The owner or operator of each vessel equipped with a closed vent system and control device meeting the specifications of § 60.112b or with emissions reduction equipment as specified in 40 CFR 65.5(b)(4), (b)(5), (b)(6), or (c) is exempt from the requirements of paragraphs (c) and (d) of this section.

§ 60.117b Delegation of authority.

(a) In delegating implementation and enforcement authority to a State under section 111(c) of the Act, the authorities contained in paragraph (b) of this section shall be retained by the Administrator and not transferred to a State.

(b) Authorities which will not be delegated to States: §§ 60.111b(f)(4), 60.114b, 60.116b(e)(3)(iii), 60.116b(e)(3)(iv), and 60.116b(f)(2)(iii).

[52 FR 11429, Apr. 8, 1987, as amended at 52 FR 22780, June 16, 1987]

**Attachment C:
Miami International Airport, Miami, Florida**

MIA Vertical Fixed Roof Tanks: Dimension and Throughput Details

#	Tank # (Emission Unit)	Status	Material Stored	Hides	Dimensions in Feet			Working	Tank Capacity			Maximum Gallons/Year			Other Tank Details		
					Height	Height	D		Max Vol	Avp Vol	Gals/year	Turnover	lb/yr	Coat/Color	Rt. Ht. Ft.	Pressure Setting	
1	#3 Tank (005-T3)	In Use	Jet Kerosene	40	38.33	29.90	53.5	630,000	644,195	502,472	400,000,000	620.93	9,523,810	White/	0.063	Atm. Set.	
2	#5 Tank (005-T5)	In Use	Jet Kerosene	40	38.416	29.96	53.5	630,000	645,641	503,600	400,000,000	619.54	9,523,810	White/	0.063	Atm. Set.	
3	#7 Tank (005-T7)	In Use	Jet Kerosene	40	37.5	31.50	82.5	1,503,600	1,498,685	1,258,896	400,000,000	266.90	9,523,810	White/	0.063	Atm. Set.	
4	#8 Tank (005-T8)	Currently not	Jet Kerosene	40	38.33	32.20	67	1,083,600	1,010,322	848,670	400,000,000	395.91	9,523,810	White/	0.063	Atm. Set.	
5	#9 Tank (005-T9)	Currently not	Jet Kerosene	40	38.33	32.20	67	1,083,600	1,010,322	848,670	400,000,000	395.91	9,523,810	White/	0.063	0.5 oz/sq in	
6	#24 Tank (005-T24)	In Use	Jet Kerosene	48	46.08	37.32	120	4,015,200	3,896,245	3,155,958	400,000,000	102.66	9,523,810	White/	0.083	0.5 oz/sq in	
7	#25 Tank (005-T25)	In Use	Jet Kerosene	48	46	29.44	120	4,015,200	3,889,480	2,489,267	400,000,000	102.84	9,523,810	White/	0.083	0.5 oz/sq in	
8	#26 Tank (005-T26)	In Use	Jet Kerosene	48	46	27.60	120	4,015,200	3,889,480	2,333,688	400,000,000	102.84	9,523,810	White/	0.083	0.5 oz/sq in	

MIA Internal Floating Roof Tanks: Dimension and Throughput Details

#	Tank # (Emission Unit)	Status	Material Stored	Hides	Dimensions in Feet			Tank Capacity			Annual Gallons		
					Height	Height	D	Theor. Volume	Max. Volume	Avp Vol	Thrup Vol	TP	lb/yr
1	#13 Tank (004-T13)	In Use	Jet Kerosene	40	37.33	35.33	70	1,155,000	1,074,052	644,431	400,000,000	372.42	9,523,810
2	#14 Tank (004-T14)	In Use	Jet Kerosene	40	37.83	35.83	70	1,155,000	1,088,438	653,063	400,000,000	367.50	9,523,810
3	#15 Tank (004-T15)	In Use	Jet Kerosene	40	35.83	35.83	60	840,000	757,392	757,392	400,000,000	528.13	9,523,810
4	#16 Tank (004-T16)	In Use	Jet Kerosene	40	35.83	35.83	60	840,000	757,392	757,392	400,000,000	528.13	9,523,810
5	#17 Tank (004-T17)	In Use	Jet Kerosene	40	35.83	35.83	60	840,000	757,392	757,392	400,000,000	528.13	9,523,810
6	#18 Tank (004-T18)	In Use	Jet Kerosene	40	35.83	35.83	60	840,000	757,392	757,392	400,000,000	528.13	9,523,810

#	Tank # (Emission Unit)	Column	Column Shell and End			Roof Design		Type	Tank Type and Features							
			Int Shell	Ext Shell	Feed	Primary	Second		Hatch	Cargo Hatch	Col. Well	Lid. Well	Rm Vent	Roof Drain	Vac. Pouch	
1	#13 Tank (004-T13)	32	Light Rust	White/Good	White/Good	Mech Shoe	--	Welded	--	Yes	Yes	Yes	Yes	Yes	--	--
2	#14 Tank (004-T14)	32	Light Rust	White/Good	White/Good	Mech Shoe	--	Welded	--	Yes	Yes	Yes	Yes	Yes	--	--
3	#15 Tank (004-T15)	9	Light Rust	White/Good	Gray/Good	Mech Shoe	--	Welded	Yes	Yes	Yes	--	Yes	Yes	Yes	
4	#16 Tank (004-T16)	14	Light Rust	White/Good	White/Good	Mech Shoe	--	Welded	Yes	Yes	Yes	--	Yes	Yes	Yes	
5	#17 Tank (004-T17)	9	Light Rust	White/Good	Gray/Good	Mech Shoe	--	Welded	Yes	Yes	Yes	--	Yes	Yes	Yes	
6	#18 Tank (004-T18)	6	Light Rust	White/Good	Gray/Good	Mech Shoe	--	Welded	Yes	Yes	Yes	--	Yes	Yes	Yes	

#	Tank #	Throughput Gals/year	PTE Emissions		Factor*1
			lbs/year	TPY *3	
1	#3 Tank	400,000,000	3,978.76	1.99	0.01
2	#5 Tank	400,000,000	3,981.47	1.99	0.01
3	#7 Tank	400,000,000	5,220.75	2.61	0.01
4	#8 Tank	400,000,000	4,496.20	2.25	0.01
5	#9 Tank	400,000,000	4,489.49	2.24	0.01
6	#24 Tank	400,000,000	6,743.17	4.37	0.02
7	#25 Tank	400,000,000	9,040.87	4.52	0.02
8	#26 Tank	400,000,000	9,122.13	4.56	0.02

#	Tank #	Throughput Gals/year	PTE Emissions		Factor*2
			lbs/year	TPY *3	
1	#13 Tank - N4	400,000,000	1,842.73	0.92	0.005
2	#14 Tank - N4	400,000,000	1,842.72	0.92	0.005
3	#15 Tank - N4	400,000,000	1,705.88	0.88	0.004
4	#16 Tank - N4	400,000,000	1,862.70	0.93	0.005
5	#17 Tank - N4	400,000,000	1,785.91	0.88	0.004
6	#18 Tank - N4	400,000,000	1,735.67	0.85	0.004

*1 Note that emission factor for Vertical Fixed Roof Tanks < 0.05 lbs/1000 gallons of throughput.

*2 Note that emission factor for Internal Floating Roof Tanks < or = 0.005 lbs/1000 gallons of throughput.

*3 Note that VOC emission estimated per tank is less than the Florida DEP's Significance Threshold for VOC of 5 TPY.