Attachment 8 - Summary of Stationary Engines on Site

Location	Manufacturer	Model No.		Purchase Date (Month-YY)	Generator Rating (KW)
Transfer Building	Cummins	QSL9-G2NR3	73036295	June-11	230
Incinerator Building	Cummins	440FDR7012	KA-926301-1/14-12	March-80	215
Scale house	Generac	DS30D6SGT	N/A	October-11	30

				40 CFR 60	40 CFR 60
			40 CFR 63 Subpart	Subpart IIII	Subpart JJJJ
Location	Engine Use	Fuel Tupe	ZZZZ Applicable?	Applicable ?	Applicable ?
1. Transfer Building	Standby/Emergency	No. 2 Fuel Oil	YES	YES	NO
2. Incinerator Building	Standby/Emergency	No. 2 Fuel Oil	YES	NO	NO
3. Scale house	Standby/Emergency	No. 2 Fuel Oil	YES	YES	NO

<u>Stationary Reciprocating Internal Combustion Engines - Applicable Operation Requirements</u>

			40 CFR 63 Subpart ZZZZ Applicable Operation	40 CFR 60 Subpart IIII Applicable Operation	
			Requirements (New Emergency CI Stationary	Requirements (NSPS for Emergency CI RICE) - 40 CFR	
Location	Manufacturer	Model No.	RICE at Area Source of HAPs)	60.4211(f)	
Transfer Building	Cummins	QSL9-G2NR3	Change oil and filter every 500 hours of operation or annually, whichever comes first; Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first, and replace as necessary; inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.	Engine must be certified. Install non-resettable hour meter. Limit of 100 hrs/yr for maintenance/readiness testing and record engine hours.	
Scale house	Generac	DS30D6SGT	Change oil and filter every 500 hours of operation or annually, whichever comes first; Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first, and replace as necessary; inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.	Engine must be certified. Install non-resettable hour meter. Limit of 100 hrs/yr for maintenance/readiness testing and record engine hours.	

Location	Manufacturer	Model No.	Requirements (EXISTING Emergency CI	40 CFR 60 Subpart IIII Applicable Operation Requirements (NSPS for Emergency CI RICE) - 40 CFR 60.4211(f)
Incinerator Building	Cummins	440FDR7012	Change oil and filter every 500 hours of operation or annually, whichever comes first; Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first, and replace as necessary; inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.	NONE