#### STATE OF FLORIDA

A029-160258

# DEPARTMENT OF ENVIRONMENTAL REGULATION

TWIN TOWERS OFFICE BUILDING 2600 BLAIR STONE ROAD TALLAHASSEE, FLORIOA 32301 D. E. R.

FEB 0 3 1989



RECEIVED

BOB GRAHAM GOVERNOR

FEB 2 1989

VICTORIA J. TSCHINKEL SECRETARY

SOUTHWEST DISTRICT E.P.C. OF H.C.

TAMPAAPPLICATION FOR RENEWAL OF PERMIT TO OPERATE AIR POLLUTION SOURCE(S)

If major alterations have occurred, the applicant should complete the Standard Air Permit Application Form.						
Sou	rce Type: Air Pollution	Renewal of DER Permit No. A029-80046				
Com	mpany Name: Tampa Electric Company	County: Hillsborough				
Ide: Kil	antify the specific emission point source In No. 4 with Venturi Scrubber; Peaking U	(s) addressed in this application (i.e., Lime nit No. 2, Gas Fired):				
F	F.J. Gannon Station Unit 5 and 6 Fly Ash	Silo				
Sou	urce Location: Street: Port Sutton Ros	ad City: Tampa				
	UTM: East 360,061	North 3,087,459				
		Longitude: 8 2° 2 5' 1 8"W.				
<i>.</i> /						
•	with operation permit fee schedule s 17-4.05.	rtment of Environmental Regulation in accordance et forth in Florida Administrative Code Rule plant since last permitted? [ ] Yes [x] No cribe on a separate sheet and attach.				
3.	Attach the last compliance test report previously. Submitted 11/21/88	required per permit conditions if not submitted				
4.	. Have previous permit conditions been adhered to? [x] Yes $[\ ]$ No $[\ ]$ If no, explain on a separate sheet and attach.					
5.		ollution control equipment during tenure of cur- and not previously reported, give brief details sheet and attach. Bag maintenance and replacement.				
6.	Has the pollution control equipment be ciency last permitted by the Department	en maintained to preserve the collection effi-				
7.	Has the annual operating report for the [x] No If no, please attach. Will h					

ປິER Form 17-1.202(4) Effective November 30, 1982

	ving information if applica	
A. Raw Materials and Che	emical Used in Your Process	: Not Applicable
Description	Contaminant Type	Utilization %Wt Rate lbs/hr
B. Product-Weicht-{lbs/	material Handling Rat	te = 13.1 tons/hr (Calculated)
C. Fuels Not Applicabl		
Type (Be Specific)	Consumption* Avg/hr* Ma	Maximum Heat x/hr++ Input (MM8TU/hr)
	only) 8760; if sessonal,	; days/wk7; wks/yr52; describe
fully aware that the state rate an air pollution sour belief. Further, the und pollution control facility 403, Florida Statutes, a derstands that a permit, i	ements made in this applice are true, correct and codersigned agrees to maintailes in such a manner as to and all the rules and regular granted by the Department upon sale or legal  Signature  Jerry L.  ation  P.O. Box code  Tampa	ot, will be non-transferable and transfer of the permitted facility  Owner or Authorized Representative Notarization is mandatory)  Williams, Director-Environmental Typed Name and Title  Address  FL. 33601
R Form 17-1.202(4) Tective November 30, 1982 TATE OF FLORIDA OUNTY OF HILLSBOROUGH worn to and subscribed bef	2/01/89  Date Page 2 of 2	(813) 228-4111 Zip  (813) Zip Stata Zip  (813) Zip Stata Zip

Notary Public Commission Expires: HY COMMISSION EXP. NOV 14,1989
BONDED THRU GENERAL INS. UND.

## F.J. GANNON STATION - UNITS 5 & 6 FLY ASH SILO

Operation and Maintenance Plan

#### INTRODUCTION

SOUTHWEST DISTRICT The steel flyash silo for Units 5 & 6 is an integral part of the particulate

control/collection system. Flyash that is collected from Units 5 and 6 ESP hoppers is transferred dry to the 25 feet diameter, 50 feet high silo. The silo acts as a temporary storage for the flyash prior to being fed into tanker-type trucks, thence transported to an offsite consumer.

Gannon's flyash is used as an ingredient in the manufacturing of cement.

#### PARTICULATE CONTROL EQUIPMENT DATA

Units 5 and 6 flyash silo is equipped with a bag-type dust collector for the control of particulate matter. The dust collector is automatically actuated during conveying, aerating or unloading operations.

Important design information and data applicable to the particulate control system are listed below:

## BACHOUSE DATA

Manufacturer Model name and number Design flow rate (ACFM) Efficiency (% of weight) Pressure drop (inch H<sub>2</sub>0) Gas Temperature (°F) Air to cloth ratio Bag material Filter cleaning method

United States Filter Corporation Mikro-Pulsaire Unit #1F3-24 11,300 99.9 2 (Clean), 5 (Dirty)

300 (average)

5:1

Polyester HCE Pulse Jet

## BAG FILTER CLEANING

Dust which accumulates on the bags is removed by a timed pulse of compressed air supplied at 18.4 scfm and 100 psig.

The filters are cleaned in sequence on a continuous basis whenever the baghouse is being operated, that is, whenever aeration is provided or dust is entering the silo.

Filters are changed whenever the pressure drop between inlet and outlet of the bag filter is approximately 5 inches of water.

RECEIVED

FEB 2 1989

E.P.C. of H.C.

#### SILO SYSTEM PERFORMANCE PARAMETERS

The following is a list of operating conditions that can be monitored from the flyash silo control panel:

- 1. Conveying blower high differential temperature
- 2. Conveying blower filter clogged
- 3. Flyash system high pressure
- 4. Silo filter bag failure
- 5. Silo level
- 6. Airlock sequency failure

The pressure drop between the inlet and outlet of the baghouse is measured with a manometer that is connected to the baghouse.

## MAINTENANCE AND INSPECTION SCHEDULES

Routine on-line preventive maintenance, daily checks for leakage, daily checks on baghouse pressure drops and monitoring of the control panel for abnormal operating conditions, ensure proper operations of the silo system. Should these procedures indicate repairs are necessary, maintenance job requests are initiated. All repair information is stored for a minimum of two years.

The pressure differential between the inlet and outlet of the bag filter is read 3 times daily. These readings are recorded in an operator's log book kept in the control room, and are retained for at least two years.

D. E. R.

FEB 0 3 1989

SOUTHWEST DISTRICT TAMPA

2-194614 CHECK NO.

194514



**POST OFFICE BOX 111** TAMPA, FLORIDA 33601

PAY:
SEVEN HUNDRED FIFTY AND NO/100 DOLLARS 01 30 89

63-27

FLORIDA DEPT OF ENVIRONMENTAL TO REJULATION

THE **ORDER** OF

NCNB NATIONAL BANK OF FLORIDA . TAMPA, FLORIDA

#194614# #063100277# 3600401262#

THE ACCOMPANYING CHECK IS IN FULL PAYMENT OF ITEMS BELOW - DETACH BEFORE CASHING

	INVOICE NO.	DATE	VOUCHER	GROSS AMOUNT	DISCOUNT	NET AMOUNT
	63 C MA	012439	513754	750.00	-	750.00
				Gannon Station Us Ash Silo	ait 5 and 6	
					DO NO HOLD FOR	U.S MAIL SEND TO CALL
					3	V8.45
-	CHECK NO.	DATE つ13009	VENDOR NO.	FLORIDA DEP	TOF ENVIR	TOTAL AMOUNT

TAMPA ELECTRIC COMPANY • P.O. BOX 111 TAMPA, FL. 33601 • (813) 228-4111

D. E. R.

..,

FEB 0 3 1989

SOUTHWEST DISTRICT TAMPA

RECEIVED

FEB 2 1989

E.P.C. of H.C.

**2-** 194608 CHECK NO.

194600

POST OFFICE BOX 111 TAMPA, FLORIDA 33601

DATE

THREE HUNDRED FIFTY FIVE AND NO/100 ## OL 30 89 DULLARS \*\*\*\*\*\*\*\*\*\*\*\*\*\*\*

TO THE

PAY:

ENVIRONMENTAL PROTECTION COMMISSION OF HILLSBORDUGH COU

**ORDER** OF

ONLY ONE SIGNATURE REQUIRED ON CHECKS OF \$2500.00 OR LESS

NCNB NATIONAL BANK OF FLORIDA . TAMPA, FLORIDA

#194608# #1063100277# 3600401262#

THE ACCOMPANYING CHECK IS IN FULL PAYMENT OF ITEMS BELOW - DETACH BEFORE CASHING

	INVOICE NO.	DATE	VOUCHER	GROSS AMOUNT	DISCOUNT	NET AMOUNT
	94N 586	012489		355.00 annon Station Uni Ash Silo		355+00
					1	T U.S. MAIL
					HOLD FOR	SEND TO CALL
-	CHECK NO. 3 - 1 9+50 8	DATE 013059	VENDOR NO.	VENDOR N	NAME AL PROTECT	TOTAL AMOUNT

TAMPA ELECTRIC COMPANY • P.O. BOX 111 TAMPA, FL. 33601 • (813) 228-4111

RECEIVED

FEB 2 1989

E.P.C. of H.C.

63-27