

Table OP-1

Operating Parameters to be Monitored and Minimum Measurement and Recording Frequencies

Operating parameters to be monitored	Minimum frequency		Control system		
	Data measurement	Data Recording	Dry scrubber followed by fabric filter	Wet scrubber	Dry Scrubber followed by fabric filter and wet scrubber
Maximum operating parameters:					
Maximum charge rate..	Continuous.....	1 x hour	✓	✓	✓
Maximum fabric filter inlet temperature.	Continuous.....	1 x minute....	✓		✓
Maximum flue gas temperature.	Continuous...	1 x minute...	✓	✓	
Minimum operating parameters:					
Minimum secondary chamber temperature	Continuous.....	1 x minute..	✓	✓	✓
Minimum dioxin/furan sorbent rate.	Hourly.....	1 x hour.....	✓		✓
Minimum HCl sorbent.... flow rate.	Hourly.....	1 x hour.....	✓		✓
Minimum mercury (Hg) sorbent flow rate.	Hourly.....	1 x hour.....	✓		✓
Minimum pressure drop across the wet scrubber or minimum horsepower or amperage to wet scrubber.	Continuous	1 x minute		✓	✓
Minimum scrubber liquor flow rate.	Continuous	1 x minute		✓	✓
Minimum scrubber liquor pH	Continuous..	1 x minute		✓	✓