



PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) ☒ COMPLAINT/DISCOVERY (CI) ☐
RE-INSPECTION (FUI) ☐ ARMS COMPLAINT NO:

AIRS ID#: 0330228 **DATE:** 1/29/2008 **ARRIVE:** 10:12 am **DEPART:** 10:44 am

FACILITY NAME: NINE MILE CLEANERS

FACILITY LOCATION: 176 E Nine Mile Rd
PENSACOLA 32534-3144

OWNER/AUTHORIZED REPRESENTATIVE: JOHN KNOTT **PHONE:** 250-456-2400

CONTACT NAME: Bruties Lindsey **PHONE:** 479-2293

ENTITLEMENT PERIOD: 3/3/2007 / 3/3/2012
(effective date) (end date)

PART I: INSPECTION COMPLIANCE STATUS (check ☒ only one box)

☒ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE

PART II: FACILITY CLASSIFICATION - Rule 62-213.300 FAC

(check ☒ only one box in A)

- | | |
|---|---|
| <p>A. 1. <u>Existing small area source</u> ☐
dry-to-dry only, $x < 140$ gal/yr
transfer only, $x < 200$ gal/yr
both types, $x < 140$ gal/yr
(constructed before 12/9/91)</p> <p>3. <u>Existing large area source</u> ☐
dry-to-dry only, $140 \leq x \leq 2,100$ gal/yr
transfer only, $200 \leq x \leq 1,800$ gal/yr
both types, $140 \leq x \leq 1,800$ gal/yr
(constructed before 12/9/91)</p> <p>5. <u>Ineligible for General Permit</u> ☐
drop store/out of business/petroleum
facility exceeds above limits</p> | <p>2. <u>New small area source</u> ☒
dry-to-dry only, $x < 140$ gal/yr
transfer only, $x < 200$ gal/yr
both types, $x < 140$ gal/yr
(constructed on or after 12/9/91)</p> <p>4. <u>New large area source</u> ☐
dry-to-dry only, $140 \leq x \leq 2,100$ gal/yr
transfer only, $200 \leq x \leq 1,800$ gal/yr
both types, $140 \leq x \leq 1,800$ gal/yr
(constructed on or after 12/9/91)</p> |
|---|---|
- B. The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 96 gallons.**

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC(check ☒ only one box
for each question)**Does the responsible official of the dry cleaning facility:**

1. Store perc, and wastes containing perc, in tightly sealed & impervious containers? ☐ Yes ☒ No ☐ N/A
2. Examine the containers for leakage? ----- ☒ Yes ☐ No ☐ N/A
3. Close and secure machine doors except during loading/unloading? ----- ☒ Yes ☐ No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal? ----- ☒ Yes ☐ No ☐ N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications? ----- ☐ Yes ☐ No ☒ N/A

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC

(Refer to Part II-A.1.-4. Classification: page 1 of 4, this form)

1. If the facility classification is a **Existing small area source**, no controls are required. **Proceed to Part V.**
2. If the facility classification is a **New small area source**, the machine should be equipped with a refrigerated condenser. **Complete section A. below.**
3. If the facility classification is a **Existing large area source**, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. **Complete both sections A and B below.** *Carbon adsorber must have been installed prior to September 22, 1993*
4. If the facility classification is a **New large area source**, the machine should be equipped with a refrigerated condenser. **Complete both sections A and B below.**

A. Has the responsible official of all existing large area & new sources:(check ☒ only one box for
each question)

1. Equipped all machines with the appropriate vent controls? ----- ☒ Yes ☐ No
2. Equipped dry-to-dry machines with a closed-loop vapor venting system? ----- ☒ Yes ☐ No ☐ N/A
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? ----- ☒ Yes ☐ No ☐ N/A
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis? ----- ☒ Yes ☐ No
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F? ----- ☐ Yes ☐ No ☒ N/A
6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged? ----- ☒ Yes ☐ No

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)**B. Does the responsible official of an existing large or new large area source also:**(check ☒ only one box for each question)

1. Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis? ----- ☐ Yes ☐ No
2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly? ----- ☐ Yes ☐ No ☐ N/A
 - a) Is the temperature differential equal to, or greater than 20° F? ----- ☐ Yes ☐ No ☐ N/A
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber? ----- ☐ Yes ☐ No ☐ N/A
 - a) Is the perc concentration equal to, or less than 100 ppm? ----- ☐ Yes ☐ No ☐ N/A
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet? ----- ☐ Yes ☐ No ☐ N/A
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils? ----- ☐ Yes ☐ No ☐ N/A
6. Route airflow to the carbon adsorber (if used) at all times? ----- ☐ Yes ☐ No ☐ N/A

PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC**Does the responsible official:**(check ☒ only one box for each question)

1. Maintain receipts for perc purchased? ----- ☒ Yes ☐ No
2. Maintain rolling monthly total of yearly perc consumption? ----- ☒ Yes ☐ No
3. Maintain leak detection inspection and repair reports for the following:
 - a) documentation of leaks repaired w/in 24 hrs? or; ----- ☒ Yes ☐ No ☐ N/A
 - b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? ----- ☐ Yes ☐ No ☒ N/A
4. Maintain calibration data? (*for applicable direct reading instruments*) ----- ☐ Yes ☐ No ☒ N/A
5. Maintain exhaust duct monitoring data on perc concentrations? ----- ☐ Yes ☐ No ☒ N/A
6. Maintain a startup/shutdown/malfunction plan? ----- ☒ Yes ☐ No
7. Maintain deviation reports? ----- ☒ Yes ☐ No ☐ N/A
 - a) Problem corrected? ----- ☒ Yes ☐ No ☐ N/A
8. Maintain a compliance plan, if applicable? ----- ☐ Yes ☐ No ☒ N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC(check ☒ only one box for each question)

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

detection and repair inspection? -----	☒ Yes	☐ No
2. Does the facility maintain a leak log? -----	☒ Yes	☐ No
3. Does the responsible official check the following areas for leaks?		
a) Hose connections, fittings, couplings, and valves -----	☒ Yes	☐ No ☐ N/A
b) Door gaskets and seating -----	☒ Yes	☐ No ☐ N/A
c) Filter gaskets and seating -----	☒ Yes	☐ No ☐ N/A
d) Pumps -----	☒ Yes	☐ No ☐ N/A
e) Solvent tanks and containers--	☒ Yes	☐ No ☐ N/A
f) Water separators -----	☒ Yes	☐ No ☐ N/A
g) Muck cookers -----	☒ Yes	☐ No ☐ N/A
h) Stills -----	☒ Yes	☐ No ☐ N/A
i) Exhaust dampers -----	☐ Yes	☐ No ☒ N/A
j) Diverter valves -----	☒ Yes	☐ No ☐ N/A
k) Cartridge filter housings	☒ Yes	☐ No ☐ N/A
4. Which method(s) of detection (is/are) used by the responsible official?		
a) Visual examination (condensed solvent on exterior surfaces) -----	a) ☒	
b) Physical detection (airflow felt through gaskets) -----	b) ☒	
c) Odor (noticeable perc odor) -----	c) ☒	
d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) -----	d) ☐ ** (see below)	
e) Halogen leak detector -----	e) ☒	
**If using direct-reading instrumentation, is the equipment: ----- ** ☐ N/A		
1) Capable of detecting perc vapor concentrations in a range of 0-500 ppm? -----	1) ☐ Yes	☐ No
2) Calibrated against a standard gas prior to and after each use (PID/FID only)? -----	2) ☐ Yes	☐ No
3) Inspected for leaks and obvious signs of wear on a weekly basis? -----	3) ☐ Yes	☐ No
4) Kept in a clean and secure area when not in use? -----	4) ☐ Yes	☐ No
5) Verified for accuracy by use of duplicate samples (calorimetric only)? -----	5) ☐ Yes	☐ No

Chris Stoll

1/29/08

Inspector's Name (Please Print)

Date of Inspection

Inspector's Signature

Approximate Date of Next Inspection

COMMENTS: An unannounced inspection was conducted on January 29th, of the Nine Mile Cleaners, located at 176 E. Nine Mile Road. During the inspection, a review of facility records was conducted, as well as a site walk through. Good records are being maintained for the operation and maintenance of the perchloroethylene dry cleaning machine. The PERC machine appeared to be well maintained. Secondary containment is provided for all units of the machine and related containers. All hazardous waste drums containing spent carbon filters and perchloroethylene waste had lids; however, they were not sealed tightly.

RECOMMENDATIONS:

Keep all containers labeled and tightly closed. All hazardous wastes, including lint and used filters must be stored in a tightly closed container. Do not let filters sit out to dry by evaporation. If the waste container has a retaining ring, it must be sealed using the ring.