

HALOGENATED SOLVENT DEGREASERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOV					
AIRS ID#: 0250983 DA	ГЕ: 10/20/2009	ARRIVE: <u>12:40 PM</u>	DEPART: <u>1:10 PM</u>				
FACILITY NAME: PRO	FACILITY NAME: PROPULSION TECHNO;OGY						
FACILITY LOCATION	8855 NW 35th Lane						
	MIAMI 33172-12	18					
OWNER/AUTHORIZED REPRESENTATIVE: MICHEL FIOT PHONE: (305)592-1044							
CONTACT NAME:		PHO	NE:				
ENTITLEMENT PERIO	DD: 12/5/2003 / 12/5/2 (effective date) (end date	2008 Facility may be operatin	g without Entitlement!				
☐ IN COMPLIANO	CE MINOR Non-CO	OMPLIANCE SIGNIFIC	ANT Non-COMPLIANCE				
PART II: NOTIFICATI (check ☑ appropriat	<u>ION</u> – Rule 62-210.300 FA e box(es))	C					
perchloroet methylene o trichloroeth 1,1,1-trichlo carbon tetra	colvent used at facility: hylene chloride pylene coroethane	Batch Vapor, x New In-line Existing In-line					
DADELIA GLAGGIELGA	TION D 1 (2 212 200)	D. C.					
PART III: <u>CLASSIFICATION</u> – Rule 62-213.300 FAC Indicate the machine type(s) observed at the facility:							
Batch Vapor, x ≤		New In-line	Batch Cold (immersion)				
Batch Vapor, x >	1.21 m ²	Existing In-line	Batch Cold (remote reservoir)				

	T IV: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC Batch Vapor and In-Line Machines			
	1. Does the facility maintain an idling and downtime mode cover that is readily opened and closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?	⊠Yes	□No	
	2. Does the facility maintain a freeboard ratio of 0.75 or greater?	⊠Yes	□No	
	3. Does the facility utilize a parts basket or parts whose size is less than 50% of the solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?	□Yes	□No	
	4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?	⊠Yes	□No	
	5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?	⊠Yes	□No	
	6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorber should not be by-passed, the lip exhaust shall be located above the closed machine cover	Yes	□No	⊠N/A
	7. Does the facility have each machine equipped with: a. a device to shut off sump heat if the solvent level drops to the heater coils? b. a device to shut off sump heat if the vapor level rises above the height of the	⊠Yes	□No	
	vapor condenser? c. a primary condenser?		□N □N	
	8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?	⊠Yes	□No	
В. <u>В</u>	1. Does the facility collect and store all waste solvent in closed containers? 2. Does the facility use a flexible hose or flushing device only within the	Yes	□No	
	freeboard area?		□No	
			□No	
			□No	
	5. Does the facility immediately clean up spills during solvent transfer? Store wipe rags in a covered container?	□Yes	□No	
	6. Does the facility operate the agitator to produce a rolling motion? (applicable only when air or pump agitated solvent bath used)	_ ∐Yes	_ □No	□N/A
	7. Does the facility ensure that the machine is not exposed to drafts greater than 40 m/min (132 ft/min) when the cover is open?	□Yes	□No	
	8. Does the facility ensure that sponges, fabrics, wood and paper products are <u>not</u> placed in the machine?	□Yes	□No	
	 Remote Reservoir Type Only 9. Does the facility employ a tightly fitting cover over the solvent sump? The cover must be closed at all times except during parts cleaning	□Yes	□No	□N/A
=	10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio of 0.75? Tightly fitting cover must be closed at all times except during parts entry and removal.	∐Yes	□No	□N/A

	PART V: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (not applicable to batch cold cleaning machines) Facility chose to meet requirements using: control device combination / work practice standards						
A.	Batch Vapor	Machines, $x \le 1.21 \text{ m}^2$					
	(Select control combination)		<u>DEVICE</u> IN <u>USE</u>				
	1. □g 2. □g 3. □g 4. □g 5. □g 6. □g 7. □g 8. □g	working mode cover reduced room draft freeboard refrig. device freeboard refrig. device	1.0 freeboard ratio -	superheated vapor superheated vapor dwell			
	9.	freeboard refrig. device carbon adsorber	carbon adsorber 1.0 freeboard ratio -	superheated vapor			
В.	Batch Vapor	Machines, $x > 1.21 \text{ m}^2$					
	(Select contro						
	combination		<u>DEVICE</u> IN <u>USE</u>				
	 □g 	freeboard refrig. device freeboard ratio	superheated vapor Superheated vapor Superheated vapor Superheated vapor Superheated vapor Feduced room draft - Feduced r	1.0 freeboard ratio working mode cover reduced room draft carbon adsorber dwell 1.0 freeboard ratio superheated vapor			
C.	Existing In-I	Line Machines					
Ī	(Select control combination)		<u>DEVICE IN USE</u>				
	1.	freeboard refrig. device superheated vapor freeboard refrig. device carbon adsorber	1.0 freeboard ratio -				
D.	New In-Line	<u>Machines</u>					
	(Select control combination)		<u>DEVICE IN USE</u>				
		freeboard refrig. device freeboard refrig. device superheated vapor	superheated vapor - carbon adsorber carbon adsorber				

PART VI: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC								
Has the responsible official maintained the following:								
 Owner's manuals, design specifications, and other instructional materials for cleaning machine and control equipment?	⊠Yes ⊠Yes ⊠Yes ⊠Yes	□No □No □No □No						
5. Dates of solvent additions and amounts added to each machine? (applicable only to those using an alternative emission limit)	□Yes	□No	⊠N/A					
6. Idling emissions limit tests, including values obtained during the initial performance test? (applicable only to those using an idling emissions limit)	□Yes	□No	⊠N/A					
7. All control device and parameter monitoring? (applicable only to batch vapor and in-line machines)	□Yes	□No	⊠N/A					
subsequent monitoring of affected parameters?	Yes	□No	⊠N/A					
9. Monthly emissions calculations (applicable only to those using an alternative or idling emission limit)	Yes	□No	⊠N/A					
10. 3-month rolling average emissions calculations? (applicable only to those using an alternative emission limit)	□Yes	□No	⊠N/A					
11. Cleaning capacity calculations? (applicable only to those using an alternative emission limit without a solvent-air interface)		□No	⊠N/A					
FRANK DELGADO 10/20/2009								
Inspector's Name (Please Print) Date of Inspection								
Inspector's Signature Approximate Date of Next	Inspection	 n						

COMMENTS: THE ENTITLEMENT PERIOD EXPIRED ON 12/5/2008. THE FACILITY IS MOVING TO MIRAMAR, FLORIDA WITHIN THREE (3) MONTHS AS PER MARCO ALVAREZ, THE FACILITY'S SUPERVISOR. THEY HAVE MOVED SOME EQUIPMENT BUT THE VAPOR DEGREASER IS STILL ON SITE AND IT IS OPERATIONAL. MR. ALVAREZ WAS TOLD TO SUBMIT A NOTIFICATION FORM TO TALLAHASSEE AS SOON AS POSSIBLE. I E-MAILED THE AIR PERMIT NOTIFICATION FORM THE SAME DAY. THE HOUSEKEEPING IS GOOD.